

## IDEM - IDEMAG - CPR SWITCH

113001  
CPR 2M '2NC'

- Polyester housing
- Narrow housing 20 mm
- Switching range 12 mm
- Loads up to 2 A
- No dedicated controller



### PRODUCT DESCRIPTION

The IDEMAG - CPR switch is a magnetic switch made of high tolerance polyester, which is ideal for all industrial applications. It allows to switch currents, depending on the model, to 1 A or 2 A. The slim switch housing - 20 mm gives the possibility of mounting in applications with a limited space for mounting. The switch is resistant to pressure washing.

### SPECIFICATIONS

Annual usage	8 cycles per hour/24hours per day/365 days
Approvals	ISO 14119, EN60947-5-1, EN60204-1, ISO 13849-1, EN62061, UL 508
Cable length	2 m
Cable type	PVC 6 or 8 core 6mm OD conductors 0.25 <sup>2</sup>
Coding	Not coded
Conductor size	0.25
Contact rating max	250Vac 1.0A
Contacts	2NC
Integrated LED indication	No
IP Class	IP69K, IP67
Mechanical reliability B10d	3.3 x 10 <sup>6</sup> operations at 100mA load
Mounting	2 x M4
MTTFd	470 years
Operating temperature	-25..80°C
PFHd	2.52 x 10 <sup>-8</sup>
PL	e acc. ISO13849-1
Recommended mounting gap	5
SIL	3 acc. EN62061
Switching current min	10Vdc 1mA

Switching distance	Sao 10mm close, Sar 22mm open
Switching frequency max	1.0Hz maximum

