



## IDEM - SAFETY NON-CONTACT SWITCH MMC-H

131101

MMC-H Right 2M '2NC'

- Stainless steel housing
- Compact dimensions
- Switching range - 10mm
- Mounting with hexagonal screws
- No dedicated controller



### Product description

A coded magnetic switch made of small size stainless steel that is ideal for use in the food and pharmaceutical industries. The switch has a standard spacing of fixing holes - 22 mm and is resistant to pressure washing. Installation with hexagonal screws makes the circuit breaker more resistant to dirt and is therefore ideal for demanding food applications.

### Specifications

<b>Approvals</b>	ISO 14119, EN60947-5-1, EN60204-1, ISO 13849-1, EN62061, UL 508
<b>Cable length</b>	2 m
<b>Cable type</b>	PVC 6 or 8 core 6mm OD conductors 0.25mm <sup>2</sup>
<b>Central Material</b>	Stainless steel 316
<b>Coding</b>	Coded magnetic actuation
<b>Conductor size</b>	0.25
<b>Contact rating max</b>	24Vdc 0.2A
<b>Contacts</b>	2NC
<b>Integrated LED indication</b>	Yes
<b>IP Class</b>	IP67, IP69K

Mounting	2 x M4
MTTFd	866 years
Operating temperature	-25..105°C
PFHd	$8.71 \times 10^{-11}$
PL	e acc. ISO13849-1
Recommended mounting gap	5
SIL	3 acc. EN62061
Switching current min	10Vdc 1mA
Switching distance	Sao 8mm close, Sar 12mm open
Switching frequency max	1.0Hz maximum

