



IDEM - NON-CONTACT SAFETY SWITCH WMC

136016
WMC QC M12 8way '2NC'

- Reinforced stainless steel housing
- High tolerance for misalignment
- Switching range - 14 mm
- Activation from the front
- No dedicated controller



Product description

Coded magnetic switch made of high tolerance stainless steel, which is ideally suited for applications in the food and pharmaceutical industries. The reinforced 32 mm wide switch housing makes it suitable for demanding applications. The switch is resistant to pressure washing.

Specifications

Approvals	ISO 14119, EN60947-5-1, EN60204-1, ISO 13849-1, EN62061, UL 508
Cable length	0.25 m
Cable type	PVC 6 or 8 core 6mm OD conductors 0.25 ²
Central Material	Stainless steel 316
Coding	Coded magnetic actuation
Conductor size	0.25
Contact rating max	24Vdc 0.2A
Contacts	2NC
Integrated LED indication	Yes
IP Class	IP67, IP69K
Mounting	2 x M4
MTTFd	866 years

Operating temperature	-25..105°C
PFHd	8.71 x 10 ⁻¹¹
PL	e acc. ISO13849-1
Recommended mounting gap	5
SIL	3 acc. EN62061
Switching current min	10Vdc 1mA
Switching distance	Sao 10mm close, Sar 20mm open
Switching frequency max	1.0Hz maximum

