IDEM - NON-CONTACT SAFETY SWITCH SMC-F

137001
SMC-F 2M '2NC' with LED



- Stainless steel housing
- Mounting screws from the bottom
- For demanding food applications
- Switching range - 14 mm
- No dedicated controller

PRODUCT DESCRIPTION

A coded magnetic switch made of stainless steel with a small size and high tolerance, which is ideally suited for applications in the food and pharmaceutical industries. The switch has a standard spacing of fixing holes - 22 mm and is resistant to pressure washing. Mounting screws from the bottom makes the switch ideal for demanding food applications.

SPECIFICATIONS

Approvals	ISO 14119, EN60947-5-1, EN60204-1, ISO 13849-1, EN62061, UL 508
Cable length	2 m
Cable type	PVC 6 or 8 core 6mm OD Conductors 0.25mm²
Coding	Coded magnetic actuation
Conductor size	0.25
Contact rating max	24Vdc 0.2A
Contacts	2NC
Integrated LED indication	Yes
IP Class	IP69K, IP67
Mounting	2 x M4
MTTFd	866 years
Operating temperature	-25..105°C
PFHd	8.71 X 10^{-11}
PL	e acc. ISO13849-1
Recommended mounting gap	5
SIL	3 acc. EN62061
Switching current min	10Vdc 1mA
Switching distance	Sao 10mm close, Sar 20mm open

Switching frequency max	1.0Hz maximum











