

## IDEM STAINLESS STEEL IP69K GUARD LOCKING SWITCH KL1-SS

220304A

KL1-SS M20 110v LED2 (lock status) - std actuator

- Solenoid locking
- Provides 4 actuator entry points
- Compact 63mm wide x 143mm long
- 2 lock monitoring safety contacts
- Rotatable head



### Product description

The KL1-SS Series Guard Locking switches have a rugged Stainless Steel 316 body and have been developed with a holding force of 1600N to keep medium to large guard doors closed until hazards have been removed.

They are designed to cope with the rigorous applications of the Food Processing, Packaging, Pharmaceutical and Petro-Chemical industries.

They have IP69K enclosure protection (maintained by a double seal lid gasket and seals) and can be high pressure hosed with detergent at high temperature.

They have a low compact body profile with fixing holes on an industry standard 40mm centre to enable easy fitting to new or existing guards (or where replacement of a non locking tongue switch is required).

The head will rotate to provide up to 4 actuator entry positions.

### Specifications

<b>Actuator</b>	Standard
<b>Annual usage</b>	8 cycles per hour/24 hours per day/365 days
<b>Approvals</b>	ISO 13849-1, ISO 14119, EN60204-1, EN62061, EN60947-5-1, UL 508
<b>Central Material</b>	Stainless steel 316
<b>Conduit entry</b>	M20
<b>Contact Type</b>	2NC safety contacts, 1NO auxiliary contact (guard open)
<b>Contacts</b>	2NC 1NO
<b>Head material</b>	Stainless steel 316
<b>Holding force (F1Max)</b>	2000





6.0 5.0 0mm

11/12	Open	
21/22	Open	
33/34		Open
43/44		Open