

## CONDUCTIVE LEVEL-PROBE - SLP SERIES

00.0008.0053

500mm length, 3xelectrodes, G1

- 1 to 4 St. Steel electrodes
- Electrodes length from 100 mm. to 1500 mm.
- Brass, St. Steel, PPL body materials
- Working pressure up to 6 bar
- Working temperature up to 100°C




### Product description

The SL conductive probe series provides a solution for controlling the level of liquid with a minimum value of conductivity of 1 $\mu$ s.


The probes are available in a wide variety of materials and process connections and are of construction appropriate to operation in extreme conditions such as those found on industrial plants.

### Specifications

<b>Electrical connection</b>	DIN A 43650
<b>Electrode Length</b>	500mm
<b>IP Class</b>	IP65
<b>Manufacturer Part No</b>	SLP.25G.3X500.K.S1
<b>Material of coatings on electrodes</b>	PVDF
<b>Material of connection</b>	Polypropylene
<b>Max. pressure</b>	6
<b>Mounting</b>	Vertical
<b>Number of electrodes</b>	3
<b>Process connection</b>	G1
<b>Temperature range to</b>	100



Electrodes length mm. L	500	1000	1500
<b>SW</b> mm	<b>A</b> mm	<b>B</b> mm	
32	63	20	
32	63	20	
40	68	20	
55	68	20	



Electrodes length mm. L	500	1000	1500
<b>SW</b> mm	<b>A</b> mm	<b>B</b> mm	
32	63	20	
32	63	20	
40	68	20	
55	68	20	