VALCO - SIDE MOUNT LEVEL SWITCH - S50 SERIES

00.0002.2755.3

Adj. length, Elbow rod, Brass/SS, 2xCO, Max 25 bar



senseca

- PP housing with PG9 electrical connection
- Micro-switch SPDT
- Max working pressure 40 bar
- Max working temperature 180°C
- Brass or St. Steel materials

Product description

These level switches, with their reduced dimensions and simplicity of installation, constitute a reliable solution for the control of liquids in all applications where it is necessary to mount a lateral type. Suitable for use with process temperature up to 180 ° C.

Specifications

Current	3A
Electrical connection	PG9 cable gland
Function	Changeover (SPDT)
Hysteresis Max	20
IP Class	IP65
Manufacturer Part No	L2.S50.7.C.25.G.O.W.I33
Material of body	Glass fiber reinforced plastic (PBT)
Material of float	Stainless steel 316
Material of seals	PTFE
Materials Wetted Parts	Stainless steel
Max. pressure	Stainless steel 25
Max. pressure	25
Max. pressure Mounting	25 Horizontal
Max. pressure Mounting Number Of Microswitches	25 Horizontal 2
Max. pressure Mounting Number Of Microswitches Process connection	25 Horizontal 2 G1
Max. pressure Mounting Number Of Microswitches Process connection Rod type	25 Horizontal 2 G1 Angled











