

## CONDUCTIVE LEVEL-PROBE - SLP SERIES

00.0008.0188

2000mm length, 1x electrode, G3/8

- 1 to 4 St. Steel electrodes
- Electrodes length from 100 mm. to 1500 mm.
- Brass, St. Steel, PPL body materials
- Working pressure up to 6 bar
- Working temperature up to 100°C




### Product description

The SL conductive probe series provides a solution for controlling the level of liquid with a minimum value of conductivity of 1µs.


The probes are available in a wide variety of materials and process connections and are of construction appropriate to operation in extreme conditions such as those found on industrial plants.

### Specifications

<b>Electrical connection</b>	DIN A 43650
<b>Electrode Length</b>	2000mm
<b>IP Class</b>	IP65
<b>Manufacturer Part No</b>	SLP.10G.1X2000.K.S1
<b>Material of coatings on electrodes</b>	PVDF
<b>Material of connection</b>	Polypropylene
<b>Max. pressure</b>	6
<b>Mounting</b>	Vertical
<b>Number of electrodes</b>	1
<b>Process connection</b>	G3/8
<b>Temperature range to</b>	100



Electrodes length mm. L	500	1000	1500
SW mm	A mm	B mm	
32	63	20	
32	63	20	
40	68	20	
55	68	20	



Electrodes length mm. L	500	1000	1500
SW mm	A mm	B mm	
32	63	20	
32	63	20	
40	68	20	
55	68	20	