

CONDUCTIVE LEVEL-PROBE - SLP SERIES

00.0008.0138

1500mm length, 1x electrode, G1/2

- 1 to 4 St. Steel electrodes
- Electrodes length from 100 mm. to 1500 mm.
- Brass, St. Steel, PPL body materials
- Working pressure up to 6 bar
- Working temperature up to 100°C




Product description

The SL conductive probe series provides a solution for controlling the level of liquid with a minimum value of conductivity of 1µs.


The probes are available in a wide variety of materials and process connections and are of construction appropriate to operation in extreme conditions such as those found on industrial plants.

Specifications

Electrical connection	DIN A 43650
Electrode Length	1500mm
IP Class	IP65
Manufacturer Part No	SLP.15G.1X1500.K.S1
Material of coatings on electrodes	PVDF
Material of connection	Polypropylene
Max. pressure	6
Mounting	Vertical
Number of electrodes	1
Process connection	G1/2
Temperature range to	100



Electrodes length mm. L	500	1000	1500
SW mm	A mm	B mm	
32	63	20	
32	63	20	
40	68	20	
55	68	20	



Electrodes length mm. L	500	1000	1500
SW mm	A mm	B mm	
32	63	20	
32	63	20	
40	68	20	
55	68	20	