

## TECNOPLASTIC - FLOAT SWITCH - TAURUS

GTAH3X106GG01

Double function, H07 RNF, 6M cable

- Internal counterweight
- 20 metres maximum depth
- Up to 60°C
- Three chamber design



### Product description

Unlike traditional floats that float on the water's surface, the Taurus level switch, thanks to its special construction of an integrated counterweight, remains under water.

The Taurus has three watertight chambers meaning it is very robust and reliable in critical applications.

Used alone or in multiples, minimum and maximum levels/high and low alarm outputs can be maintained and adjusted easily.

- Drainage plants
- Pumping stations
- Dirty water systems.

### Specifications

#### Approvals

CE, EAC, TÜV

|                          |                                |
|--------------------------|--------------------------------|
| Cable length             | 6 m                            |
| Cable type               | H07RN-F                        |
| Contact Angle            | 20                             |
| Depth-Max                | 20 m                           |
| Fixing kit included      | No                             |
| Function                 | Changeover (SPDT)              |
| Insulation class         | I                              |
| IP Class                 | IP68                           |
| Material of float        | Polypropylene                  |
| Operating temperature to | 50                             |
| Rated Current            | 8                              |
| Specific gravity         | 0.95 - 1.05 kg/dm <sup>3</sup> |
| Supply Voltage           | 250                            |

