



SUCO 0184/0185 PRESSURE SWITCH STAINLESS STEEL

Stainless steel body

0185460031486

50..200 bar, G1/4, CO, NBR, DIN, Stainless steel

- Up to 250 V
- Connector included (DIN 43650/Form A)
- Five adjustment ranges from 0,5..5 bar to 50..200 bar
- Changeover (SPDT)
- Over pressure safety of 300 bar or 600 bar



Product description

The 0184/0185 series is part of the changeover contact range from SUCO with an integrated plastic body and connector. Offering a maximum voltage of 250 V with a normally open and normally closed contact housed in a hex 27 stainless steel body offering a high pressure resistance. The switch point is very stable even after a long period of time and high load and is also adjustable on site and can come pre-set.

Common applications include power packs, mobile hydraulics, water systems, hydraulics generally and pneumatics.

Specifications

Adjustment range max	200
Adjustment range min	50
Approvals	CSA US, RoHS II
Contact load max ac	4
Contact load max dc	0.25
Deviation max	±5,0
Electrical connection	DIN EN 175301-803-A
Function	Changeover (SPDT)
IP Class	IP65
Material of body	Stainless steel
Materials Wetted Parts	Stainless steel, NBR
Max switching frequency/min	200
Max. pressure	600

Membrane Material	NBR
Process connection	1/4 BSP
Temperature ambient from	-20
Temperature ambient to	80
Temperature range of media from	-40
Temperature range of media to	100
Weight	130
Voltage AC / DC Max	250
Voltage AC / DC Min	10

