



## SUCO - 0240/0241 PRESSURE SWITCH

Pre-cabled (2m)

0240461032012

20..50 bar, G1/4, CO, EPDM, 2M cable

- Up to 250 V depending on connection
- Pre-cabled at 2 metres
- Five adjustable ranges from 0,3..1,5 bar to 50..150 bar
- Changeover (SPDT)
- Over pressure safety of 300 bar or 600 bar



### Product description

The 0240/0241 series is a pre-cabled (2 meters) pressure switch and is part of the changeover contact range from SUCO. Offering a maximum voltage of 42 V or 250 V (depending on connection) with a normally open and normally closed contact housed in a hex 27 zinc plated body offering a high pressure resistance. The switch point is very stable even after a long period of time and high load and is also adjustable on site and can come pre-set.

Common applications include commercial vehicles, mobile hydraulics, excavators etc

### Specifications

Adjustment range max	50
Adjustment range min	20
Approvals	RoHS II, CE
Contact Rating Max	2
Deviation max	±2.0
Electrical connection	Embedded 2m cable
Function	Changeover (SPDT)
IP Class	IP67
Material of body	Zinc-plated steel
Materials Wetted Parts	Zinc-plated steel, EPDM
Max switching frequency/min	200
Max. pressure	300
Membrane Material	EPDM
Process connection	1/4 BSP
Temperature ambient from	-20

Temperature ambient to	80
Temperature range of media from	-30
Temperature range of media to	120
Weight	120

