



SUCO - 0500/0501 ELECTRONIC PRESSURE SWITCH

Factory set

0500200411002

0..2 bar, G1/4, No, PNP, NBR, M12

- Single switch point
- Small & compact
- Ceramic sensor
- Stainless steel housing

PRODUCT DESCRIPTION

The SUCO 0500/0501 performance series electronic pressure switch offers a small compact electronic switch without compromising on quality which comes factory set (unadjustable by the user) with overpressure protection (up to 2x), has a long service life and is also attractively priced especially at high volumes. Using a ceramic sensor in thick film technology for a good operating temperature range and accuracy, there are six standard pressure ranges starting from 0..2 bar all the way up to 0..100 bar and a hysteresis of 1%-98%, available in normally open or normally closed with a PNP transistor output. The wetted parts are made of ceramic, stainless steel and either NBR, EPDM OR FKM ensuring excellent media compatibility, with six standard electrical connection options including Deutsch, DIN and M12 combined with two standard thread type options.

Customer specific solutions are also available on request.



Application examples

- Automotive
- Braking systems
- Medical
- Mobile hydraulics
- Off highway
- Off-shore
- Rail

SPECIFICATIONS

Accuracy	±0.5 % of adjustment range (Full scale) at room temperature
----------	---

Adjustment range max	2
Adjustment range min	0
Burst Pressure	8
EMC	EMC 2014/30/EU; EN 61000-6-2:2005; EN 61000-6-3:2007
Hysteresis	1...98% full scale, programmable at factory (maximum tolerance $\pm 1.0\%$ of adjustment range nominal pressure)
IP Class	IP67
Lifespan Mechanical	5,000,000 pulsations at rise rates to 1 bar/ms nominal pressure
Long-Term Stability	$\pm 0.1\%$ of adjustment range (full scale) per year
Max. pressure	4
Output	PNP
Pressure rise	≤ 1 bar/ms
Repeatability & Reproducibility	$\pm 0.1\%$ of adjustment range (full scale)
Supply Voltage DC Max	32
Supply Voltage DC Min	9.6
Switching point adjustment range	2...100 % of adjustment range(full scale), set at factory
Switching time	< 4 ms
Temperature ambient from	-30
Temperature ambient to	100
Temperature range of media from	-30
Temperature range of media to	100
Weight	80



DIN EN 175301-809 A	M 12 - DIN EN 61076-2-001 A	ISO 15179-A1-4.1																														
<table border="1"> <thead> <tr> <th>Pin</th> <th>Assignment</th> </tr> </thead> <tbody> <tr><td>1</td><td>U_{IN}</td></tr> <tr><td>2</td><td>GND</td></tr> <tr><td>3</td><td>U_{IN}</td></tr> <tr><td>PE</td><td>PE</td></tr> </tbody> </table>	Pin	Assignment	1	U _{IN}	2	GND	3	U _{IN}	PE	PE	<table border="1"> <thead> <tr> <th>Pin</th> <th>Assignment</th> </tr> </thead> <tbody> <tr><td>1</td><td>U_{IN}</td></tr> <tr><td>2</td><td>PE</td></tr> <tr><td>3</td><td>GND</td></tr> <tr><td>4</td><td>U_{IN}</td></tr> </tbody> </table>	Pin	Assignment	1	U _{IN}	2	PE	3	GND	4	U _{IN}	<table border="1"> <thead> <tr> <th>Pin</th> <th>Assignment</th> </tr> </thead> <tbody> <tr><td>1</td><td>U_{IN}</td></tr> <tr><td>2</td><td>NC</td></tr> <tr><td>3</td><td>GND</td></tr> <tr><td>4</td><td>U_{IN}</td></tr> </tbody> </table>	Pin	Assignment	1	U _{IN}	2	NC	3	GND	4	U _{IN}
Pin	Assignment																															
1	U _{IN}																															
2	GND																															
3	U _{IN}																															
PE	PE																															
Pin	Assignment																															
1	U _{IN}																															
2	PE																															
3	GND																															
4	U _{IN}																															
Pin	Assignment																															
1	U _{IN}																															
2	NC																															
3	GND																															
4	U _{IN}																															
IP65 ● - 60 mm shielded copper cable ▲ - 77 mm shielded copper cable Order number: 013	IP67 ● - 54 mm Order number: 002	IP67 IP69K ● - 56 mm Order number: 004																														
AMP Supersaal 1.5*	Deutsch DF04-SP	Cable connection																														
<table border="1"> <thead> <tr> <th>Pin</th> <th>Assignment</th> </tr> </thead> <tbody> <tr><td>1</td><td>U_{IN}</td></tr> <tr><td>2</td><td>GND</td></tr> <tr><td>3</td><td>U_{IN}</td></tr> </tbody> </table>	Pin	Assignment	1	U _{IN}	2	GND	3	U _{IN}	<table border="1"> <thead> <tr> <th>Pin</th> <th>Assignment</th> </tr> </thead> <tbody> <tr><td>A</td><td>U_{IN}</td></tr> <tr><td>B</td><td>GND</td></tr> <tr><td>C</td><td>U_{IN}</td></tr> </tbody> </table>	Pin	Assignment	A	U _{IN}	B	GND	C	U _{IN}	<table border="1"> <thead> <tr> <th>Pin</th> <th>Assignment</th> </tr> </thead> <tbody> <tr><td>red</td><td>U_{IN}</td></tr> <tr><td>white</td><td>U_{IN}</td></tr> <tr><td>black</td><td>GND</td></tr> </tbody> </table>	Pin	Assignment	red	U _{IN}	white	U _{IN}	black	GND						
Pin	Assignment																															
1	U _{IN}																															
2	GND																															
3	U _{IN}																															
Pin	Assignment																															
A	U _{IN}																															
B	GND																															
C	U _{IN}																															
Pin	Assignment																															
red	U _{IN}																															
white	U _{IN}																															
black	GND																															
IP67 ● - 60 mm Order number: 007	IP67 IP69K ● - 61 mm Order number: 010	IP67 ● - 42 mm (+ 25 mm shield relief) Cable length - 2 m Order number: 011																														
Thread code: 41	Thread code: 39																															

hex 24

no / nc	
○ 1	(+)
○ 2	(GND)
○ 3	(OUT)

DIN EN 175301-809 A	M 12 - DIN EN 61076-2-001 A	ISO 15179-A1-4.1																														
<table border="1"> <thead> <tr> <th>Pin</th> <th>Assignment</th> </tr> </thead> <tbody> <tr><td>1</td><td>U_{IN}</td></tr> <tr><td>2</td><td>GND</td></tr> <tr><td>3</td><td>U_{IN}</td></tr> <tr><td>PE</td><td>PE</td></tr> </tbody> </table>	Pin	Assignment	1	U _{IN}	2	GND	3	U _{IN}	PE	PE	<table border="1"> <thead> <tr> <th>Pin</th> <th>Assignment</th> </tr> </thead> <tbody> <tr><td>1</td><td>U_{IN}</td></tr> <tr><td>2</td><td>PE</td></tr> <tr><td>3</td><td>GND</td></tr> <tr><td>4</td><td>U_{IN}</td></tr> </tbody> </table>	Pin	Assignment	1	U _{IN}	2	PE	3	GND	4	U _{IN}	<table border="1"> <thead> <tr> <th>Pin</th> <th>Assignment</th> </tr> </thead> <tbody> <tr><td>1</td><td>U_{IN}</td></tr> <tr><td>2</td><td>NC</td></tr> <tr><td>3</td><td>GND</td></tr> <tr><td>4</td><td>U_{IN}</td></tr> </tbody> </table>	Pin	Assignment	1	U _{IN}	2	NC	3	GND	4	U _{IN}
Pin	Assignment																															
1	U _{IN}																															
2	GND																															
3	U _{IN}																															
PE	PE																															
Pin	Assignment																															
1	U _{IN}																															
2	PE																															
3	GND																															
4	U _{IN}																															
Pin	Assignment																															
1	U _{IN}																															
2	NC																															
3	GND																															
4	U _{IN}																															
IP65 ● - 60 mm shielded copper cable ▲ - 77 mm shielded copper cable Order number: 013	IP67 ● - 54 mm Order number: 002	IP67 IP69K ● - 56 mm Order number: 004																														
AMP Supersaal 1.5*	Deutsch DF04-SP	Cable connection																														
<table border="1"> <thead> <tr> <th>Pin</th> <th>Assignment</th> </tr> </thead> <tbody> <tr><td>1</td><td>U_{IN}</td></tr> <tr><td>2</td><td>GND</td></tr> <tr><td>3</td><td>U_{IN}</td></tr> </tbody> </table>	Pin	Assignment	1	U _{IN}	2	GND	3	U _{IN}	<table border="1"> <thead> <tr> <th>Pin</th> <th>Assignment</th> </tr> </thead> <tbody> <tr><td>A</td><td>U_{IN}</td></tr> <tr><td>B</td><td>GND</td></tr> <tr><td>C</td><td>U_{IN}</td></tr> </tbody> </table>	Pin	Assignment	A	U _{IN}	B	GND	C	U _{IN}	<table border="1"> <thead> <tr> <th>Pin</th> <th>Assignment</th> </tr> </thead> <tbody> <tr><td>red</td><td>U_{IN}</td></tr> <tr><td>white</td><td>U_{IN}</td></tr> <tr><td>black</td><td>GND</td></tr> </tbody> </table>	Pin	Assignment	red	U _{IN}	white	U _{IN}	black	GND						
Pin	Assignment																															
1	U _{IN}																															
2	GND																															
3	U _{IN}																															
Pin	Assignment																															
A	U _{IN}																															
B	GND																															
C	U _{IN}																															
Pin	Assignment																															
red	U _{IN}																															
white	U _{IN}																															
black	GND																															
IP67 ● - 60 mm Order number: 007	IP67 IP69K ● - 61 mm Order number: 010	IP67 ● - 42 mm (+ 25 mm shield relief) Cable length - 2 m Order number: 011																														
Thread code: 41	Thread code: 39																															