



## SUCO - 0500/0501 ELECTRONIC PRESSURE SWITCH

Factory set

0501161413002

0..16 bar, G1/4, Nc, PNP, FKM, M12

- Single switch point
- Small & compact
- Ceramic sensor
- Stainless steel housing

### Product description

The SUCO 0500/0501 performance series electronic pressure switch offers a small compact electronic switch without compromising on quality which comes factory set (unadjustable by the user) with overpressure protection (up to 2x), has a long service life and is also attractively priced especially at high volumes. Using a ceramic sensor in thick film technology for a good operating temperature range and accuracy, there are six standard pressure ranges starting from 0.2 bar all the way up to 0..100 bar and a hysteresis of 1%-98%, available in normally open or normally closed with a PNP transistor output. The wetted parts are made of ceramic, stainless steel and either NBR, EPDM OR FKM ensuring excellent media compatibility, with six standard electrical connection options including Deutsch, DIN and M12 combined with two standard thread type options.

Customer specific solutions are also available on request.



### Application examples

- Automotive
- Braking systems
- Medical
- Mobile hydraulics
- Off highway
- Off-shore
- Rail

## Specifications

<b>Accuracy</b>	±0.5 % of adjustment range (Full scale) at room temperature
<b>Adjustment range max</b>	16
<b>Adjustment range min</b>	0
<b>Burst Pressure</b>	60
<b>Electrical connection</b>	M12x1
<b>EMC</b>	EMC 2014/30/EU; EN 61000-6-2:2005; EN 61000-6-3:2007
<b>Function</b>	Normally Closed (SPST)
<b>Hysteresis</b>	1...98% full scale, programmable at factory (maximum tolerance ±1.0% of adjustment range nominal pressure)
<b>IP Class</b>	IP67
<b>Lifespan Mechanical</b>	5,000,000 pulsations at rise rates to 1 bar/ms nominal pressure
<b>Long-Term Stability</b>	±0.1 % of adjustment range (full scale) per year
<b>Material of body</b>	Stainless steel 1.4305
<b>Materials Wetted Parts</b>	FKM, Stainless steel 1.4305
<b>Max. pressure</b>	40
<b>Membrane Material</b>	FKM
<b>Output</b>	PNP
<b>Pressure rise</b>	≤ 1 bar/ms
<b>Process connection</b>	G1/4
<b>Repeatability &amp; Reproducibility</b>	±0.1 % of adjustment range (full scale)
<b>Shock Resistance</b>	500m / s <sup>2</sup> ; 11 ms half sine wave; DIN EN 60068-2-27
<b>Supply Voltage DC Max</b>	32
<b>Supply Voltage DC Min</b>	9.6
<b>Switching point adjustment range</b>	2...100 % of adjustment range(full scale), set at factory

Switching time	< 4 ms
Temperature ambient from	-30
Temperature ambient to	100
Temperature range of media from	-20
Temperature range of media to	125
Weight	80
Vibration Resistance	20g: 4..2000 Hz sine wave, DIN EN 60068-2-6



DIN EN 175301-800-A

Pin	Assignment
1	U <sub>in</sub>
2	Gnd
3	U <sub>out</sub>
4	U <sub>in</sub>

PSL

• 50 mm axial/cable angle  
• 17 mm axial/cable angle

Order number: 013

M 12 - DIN EN 61076-2-101-A

Pin	Assignment
1	U <sub>in</sub>
2	nc
3	Gnd
4	U <sub>out</sub>

PSL

• 54 mm

Order number: 002

ISO 15179-A1-4:1

Pin	Assigne
1	U <sub>in</sub>
2	nc
3	Gnd
4	U <sub>out</sub>

PSL PSKMK

• 50 mm

Order number: 004

AMP Supersseal 1.5"

Pin	Assignment
1	U <sub>in</sub>
2	Gnd
3	U <sub>out</sub>

PSL

• 50 mm

Order number: 007

Deutsch DT04-SP

Pin	Assignment
A	U <sub>in</sub>
B	Gnd
C	U <sub>out</sub>

PSL PSKMK

• 50 mm

Order number: 010

Cable connection

Pin	Assignment
red	U <sub>in</sub>
white	U <sub>out</sub>
black	Gnd

PSL

• 50 mm  
• 25 mm Speed lead  
Cable length: ~ 2 m

Order number: 011

Thread code: 41

Thread code: 00



<p>DIN EN 175301-800-A</p> <p>Pin Assignment</p> <table><tr><td>1</td><td>U<sub>in</sub></td></tr><tr><td>2</td><td>Gnd</td></tr><tr><td>3</td><td>U<sub>out</sub></td></tr><tr><td>4</td><td>U<sub>in</sub></td></tr></table> <p>Order number: 013</p>	1	U <sub>in</sub>	2	Gnd	3	U <sub>out</sub>	4	U <sub>in</sub>	<p>M 12 - DIN EN 61076-2-101 A</p> <p>Pin Assignment</p> <table><tr><td>1</td><td>U<sub>in</sub></td></tr><tr><td>2</td><td>nc</td></tr><tr><td>3</td><td>Gnd</td></tr><tr><td>4</td><td>U<sub>out</sub></td></tr></table> <p>Order number: 002</p>	1	U <sub>in</sub>	2	nc	3	Gnd	4	U <sub>out</sub>	<p>ISO 15179-A1-4:1</p> <p>Pin Assignment</p> <table><tr><td>1</td><td>U<sub>in</sub></td></tr><tr><td>2</td><td>nc</td></tr><tr><td>3</td><td>Gnd</td></tr><tr><td>4</td><td>U<sub>out</sub></td></tr></table> <p>Order number: 004</p>	1	U <sub>in</sub>	2	nc	3	Gnd	4	U <sub>out</sub>
1	U <sub>in</sub>																									
2	Gnd																									
3	U <sub>out</sub>																									
4	U <sub>in</sub>																									
1	U <sub>in</sub>																									
2	nc																									
3	Gnd																									
4	U <sub>out</sub>																									
1	U <sub>in</sub>																									
2	nc																									
3	Gnd																									
4	U <sub>out</sub>																									
<p>AMP Supersseal 1.5"</p> <p>Pin Assignment</p> <table><tr><td>1</td><td>U<sub>in</sub></td></tr><tr><td>2</td><td>Gnd</td></tr><tr><td>3</td><td>U<sub>out</sub></td></tr></table> <p>Order number: 007</p>	1	U <sub>in</sub>	2	Gnd	3	U <sub>out</sub>	<p>Deutsch DT04-SP</p> <p>Pin Assignment</p> <table><tr><td>A</td><td>U<sub>in</sub></td></tr><tr><td>B</td><td>Gnd</td></tr><tr><td>C</td><td>U<sub>out</sub></td></tr></table> <p>Order number: 010</p>	A	U <sub>in</sub>	B	Gnd	C	U <sub>out</sub>	<p>Cable connection</p> <p>Pin Assignment</p> <table><tr><td>red</td><td>U<sub>in</sub></td></tr><tr><td>white</td><td>U<sub>out</sub></td></tr><tr><td>black</td><td>Gnd</td></tr></table> <p>Order number: 011</p>	red	U <sub>in</sub>	white	U <sub>out</sub>	black	Gnd						
1	U <sub>in</sub>																									
2	Gnd																									
3	U <sub>out</sub>																									
A	U <sub>in</sub>																									
B	Gnd																									
C	U <sub>out</sub>																									
red	U <sub>in</sub>																									
white	U <sub>out</sub>																									
black	Gnd																									
<p>Thread code: 41</p>	<p>Thread code: 00</p>																									