



# SUCO - 0601/0602 PRESSURE SENSOR

## Performance series

0602101413010  
4-20mA, 0..10 bar, G1/4-E, FKM, Deutsch DT04-3P

- Measuring range up to 100 bar
- Ceramic sensor
- Small and compact
- Stainless steel housing



### Product description

The SUCO 0601/0602 performance series pressure sensor is a small, compact and cost effective pressure monitoring solution. Offering six standard pressure ranges with options of four different electrical connectors a thread of G1/4 and 0-10V or 4-20mA outputs. The 06 series uses a ceramic sensor in thick film technology which is housed in a stainless steel body.

Common applications include mobile hydraulics and power packs.

### Specifications

Accuracy	±1% FS
Burst Pressure	35
Connection Thread	G1/4-E
Electrical connection	Deutsch DT04-3P
IP Class	IP67, IP6K9K
Lifespan Mechanical	5 million cycles
Long-Term Stability	±0.3% FS p.a.
Material of body	Stainless steel 1.4305
Materials Wetted Parts	Stainless steel 1.4305, Ceramic, FKM
Overpressure protection	20 bar
Pressure Range Max	10
Pressure Range Min	0

Pressure reference	Gauge
Pressure rise	1 bar/ms
Repeatability & Reproducibility	±0.1% FS
Response Time	2
Shock Resistance	500m / s <sup>2</sup> ; 11 ms half sine wave; DIN EN 60068-2-27
Signal type	4-20 mA
Supply Voltage DC Max	32
Supply Voltage DC Min	9.6
Temperature ambient from	-30
Temperature ambient to	100
Temperature error	±0.04% FS/°C
Temperature range of media from	-20
Temperature range of media to	125
Weight	80
Vibration Resistance	20g: 4..2000 Hz sine wave, DIN EN 60068-2-6



<b>DIN EN 175301-803-A</b>  <table border="1"> <tr><th>Pin</th><th>0601</th><th>0602</th></tr> <tr><td>1</td><td>Uv+</td><td>Uv+</td></tr> <tr><td>2</td><td>Gnd</td><td>I<sub>ref</sub></td></tr> <tr><td>3</td><td>U<sub>ref</sub></td><td>nc*</td></tr> </table> <p>IP65  x ~ 60 mm without coupler socket  x ~ 77 mm with coupler socket  Order number: 013</p>	Pin	0601	0602	1	Uv+	Uv+	2	Gnd	I <sub>ref</sub>	3	U <sub>ref</sub>	nc*	<b>M 12 - DIN EN 61076-2-101 A</b>  <table border="1"> <tr><th>Pin</th><th>0601</th><th>0602</th></tr> <tr><td>1</td><td>Uv+</td><td>Uv+</td></tr> <tr><td>2</td><td>U<sub>ref</sub></td><td>nc*</td></tr> <tr><td>3</td><td>Gnd</td><td>I<sub>ref</sub></td></tr> <tr><td>4</td><td>nc*</td><td>nc*</td></tr> </table> <p>IP67  x ~ 54 mm  Order number: 002</p>	Pin	0601	0602	1	Uv+	Uv+	2	U <sub>ref</sub>	nc*	3	Gnd	I <sub>ref</sub>	4	nc*	nc*	<b>ISO 15170-A1-4.1</b>  <table border="1"> <tr><th>Pin</th><th>0601</th><th>0602</th></tr> <tr><td>1</td><td>Uv+</td><td>Uv+</td></tr> <tr><td>2</td><td>Gnd</td><td>nc*</td></tr> <tr><td>3</td><td>U<sub>ref</sub></td><td>I<sub>ref</sub></td></tr> <tr><td>4</td><td>nc*</td><td>nc*</td></tr> </table> <p>IP67, IP69K  x ~ 56 mm  Order number: 004</p>	Pin	0601	0602	1	Uv+	Uv+	2	Gnd	nc*	3	U <sub>ref</sub>	I <sub>ref</sub>	4	nc*	nc*
Pin	0601	0602																																										
1	Uv+	Uv+																																										
2	Gnd	I <sub>ref</sub>																																										
3	U <sub>ref</sub>	nc*																																										
Pin	0601	0602																																										
1	Uv+	Uv+																																										
2	U <sub>ref</sub>	nc*																																										
3	Gnd	I <sub>ref</sub>																																										
4	nc*	nc*																																										
Pin	0601	0602																																										
1	Uv+	Uv+																																										
2	Gnd	nc*																																										
3	U <sub>ref</sub>	I <sub>ref</sub>																																										
4	nc*	nc*																																										
<b>AMP Superseal 1.5*</b>  <table border="1"> <tr><th>Pin</th><th>0601</th><th>0602</th></tr> <tr><td>1</td><td>U<sub>ref</sub></td><td>nc*</td></tr> <tr><td>2</td><td>Gnd</td><td>I<sub>ref</sub></td></tr> <tr><td>3</td><td>Uv+</td><td>Uv+</td></tr> </table> <p>IP67  x ~ 61 mm  Order number: 007</p>	Pin	0601	0602	1	U <sub>ref</sub>	nc*	2	Gnd	I <sub>ref</sub>	3	Uv+	Uv+	<b>Deutsch DT04-3P</b>  <table border="1"> <tr><th>Pin</th><th>0601</th><th>0602</th></tr> <tr><td>A</td><td>Uv+</td><td>Uv+</td></tr> <tr><td>B</td><td>Gnd</td><td>nc*</td></tr> <tr><td>C</td><td>U<sub>ref</sub></td><td>I<sub>ref</sub></td></tr> </table> <p>IP67, IP69K  x ~ 61 mm  Order number: 010</p>	Pin	0601	0602	A	Uv+	Uv+	B	Gnd	nc*	C	U <sub>ref</sub>	I <sub>ref</sub>																			
Pin	0601	0602																																										
1	U <sub>ref</sub>	nc*																																										
2	Gnd	I <sub>ref</sub>																																										
3	Uv+	Uv+																																										
Pin	0601	0602																																										
A	Uv+	Uv+																																										
B	Gnd	nc*																																										
C	U <sub>ref</sub>	I <sub>ref</sub>																																										





Order number: 010

