



SUCO - 0601/0602 PRESSURE SENSOR

Performance series

0602401411013
4-20mA, 0..40 bar, G1/4-E, NBR, DIN

- Measuring range up to 100 bar
- Ceramic sensor
- Small and compact
- Stainless steel housing



Product description

The SUCO 0601/0602 performance series pressure sensor is a small, compact and cost effective pressure monitoring solution. Offering six standard pressure ranges with options of four different electrical connectors a thread of G1/4 and 0-10V or 4-20mA outputs. The 06 series uses a ceramic sensor in thick film technology which is housed in a stainless steel body.

Common applications include mobile hydraulics and power packs.


Specifications

Accuracy	±1% FS
Burst Pressure	140
Connection Thread	G1/4-E
Electrical connection	DIN EN 175301-803-A
IP Class	IP65
Lifespan Mechanical	5 million cycles
Long-Term Stability	±0.3% FS p.a.
Material of body	Stainless steel 1.4305
Materials Wetted Parts	Stainless steel 1.4305, Ceramic, NBR
Overpressure protection	100 bar
Pressure Range Max	40
Pressure Range Min	0

Pressure reference	Gauge
Pressure rise	1 bar/ms
Repeatability & Reproducibility	±0.1% FS
Response Time	2
Shock Resistance	500m / s ² ; 11 ms half sine wave; DIN EN 60068-2-27
Signal type	4-20 mA
Supply Voltage DC Max	32
Supply Voltage DC Min	9.6
Temperature ambient from	-30
Temperature ambient to	100
Temperature error	±0.04% FS/°C
Temperature range of media from	-30
Temperature range of media to	100
Weight	110
Vibration Resistance	20g: 4..2000 Hz sine wave, DIN EN 60068-2-6



DIN EN 175301-803-A <table><tr><th>Pin</th><th>0601</th><th>0602</th></tr><tr><td>1</td><td>U_{v+}</td><td>U_{v+}</td></tr><tr><td>2</td><td>Gnd</td><td>U_{ref}</td></tr><tr><td>3</td><td>U_{ref}</td><td>nc*</td></tr></table> <p>IP65 x ~ 60 mm without coupler socket x ~ 77 mm with coupler socket Order number: 013</p>	Pin	0601	0602	1	U _{v+}	U _{v+}	2	Gnd	U _{ref}	3	U _{ref}	nc*	M 12 - DIN EN 61076-2-101 A <table><tr><th>Pin</th><th>0601</th><th>0602</th></tr><tr><td>1</td><td>U_{v+}</td><td>U_{v+}</td></tr><tr><td>2</td><td>U_{ref}</td><td>nc*</td></tr><tr><td>3</td><td>Gnd</td><td>I_{ref}</td></tr><tr><td>4</td><td>nc*</td><td>nc*</td></tr></table> <p>IP67 x ~ 54 mm Order number: 002</p>	Pin	0601	0602	1	U _{v+}	U _{v+}	2	U _{ref}	nc*	3	Gnd	I _{ref}	4	nc*	nc*	ISO 15170-A1-4.1 <table><tr><th>Pin</th><th>0601</th><th>0602</th></tr><tr><td>1</td><td>U_{v+}</td><td>U_{v+}</td></tr><tr><td>2</td><td>Gnd</td><td>nc*</td></tr><tr><td>3</td><td>U_{ref}</td><td>I_{ref}</td></tr><tr><td>4</td><td>nc*</td><td>nc*</td></tr></table> <p>IP67, IP69K x ~ 56 mm Order number: 004</p>	Pin	0601	0602	1	U _{v+}	U _{v+}	2	Gnd	nc*	3	U _{ref}	I _{ref}	4	nc*	nc*
Pin	0601	0602																																										
1	U _{v+}	U _{v+}																																										
2	Gnd	U _{ref}																																										
3	U _{ref}	nc*																																										
Pin	0601	0602																																										
1	U _{v+}	U _{v+}																																										
2	U _{ref}	nc*																																										
3	Gnd	I _{ref}																																										
4	nc*	nc*																																										
Pin	0601	0602																																										
1	U _{v+}	U _{v+}																																										
2	Gnd	nc*																																										
3	U _{ref}	I _{ref}																																										
4	nc*	nc*																																										
AMP Superseal 1.5* <table><tr><th>Pin</th><th>0601</th><th>0602</th></tr><tr><td>1</td><td>U_{ref}</td><td>nc*</td></tr><tr><td>2</td><td>Gnd</td><td>I_{ref}</td></tr><tr><td>3</td><td>U_{v+}</td><td>U_{v+}</td></tr></table> <p>IP67 x ~ 61 mm Order number: 007</p>	Pin	0601	0602	1	U _{ref}	nc*	2	Gnd	I _{ref}	3	U _{v+}	U _{v+}	Deutsch DT04-3P <table><tr><th>Pin</th><th>0601</th><th>0602</th></tr><tr><td>A</td><td>U_{v+}</td><td>U_{v+}</td></tr><tr><td>B</td><td>Gnd</td><td>nc*</td></tr><tr><td>C</td><td>U_{ref}</td><td>I_{ref}</td></tr></table> <p>IP67, IP69K x ~ 61 mm Order number: 010</p>	Pin	0601	0602	A	U _{v+}	U _{v+}	B	Gnd	nc*	C	U _{ref}	I _{ref}																			
Pin	0601	0602																																										
1	U _{ref}	nc*																																										
2	Gnd	I _{ref}																																										
3	U _{v+}	U _{v+}																																										
Pin	0601	0602																																										
A	U _{v+}	U _{v+}																																										
B	Gnd	nc*																																										
C	U _{ref}	I _{ref}																																										





DIN EN 175301-803-A		
Pin	0601	0602
1	U _{ve}	U _{ve}
2	Gnd	I _{ut}
3	U _{ut}	nc*
IP65		
x ~ 60 mm without coupler socket x ~ 77 mm with coupler socket		
Order number: 013		

AMP Superseal 1.5*		
Pin	0601	0602
1	U _{ut}	nc*
2	Gnd	I _{ut}
3	U _{ve}	U _{ve}
IP67		
x ~ 61 mm		
Order number: 007		

M 12 - DIN EN 61076-2-101 A		
Pin	0601	0602
1	U _{ve}	U _{ve}
2	U _{ut}	nc*
3	Gnd	I _{ut}
4	nc*	nc*
IP67		
x ~ 54 mm		
Order number: 002		

Deutsch DT04-3P		
Pin	0601	0602
A	U _{ve}	U _{ve}
B	Gnd	nc*
C	U _{ut}	I _{ut}
IP67, IP6X3K		
x ~ 61 mm		
Order number: 010		

ISO 15170-A1-4.1		
Pin	0601	0602
1	U _{ve}	U _{ve}
2	Gnd	nc*
3	U _{ut}	I _{ut}
4	nc*	nc*
IP67, IP6X3K		
x ~ 56 mm		
Order number: 004		

