## ESI - GS4000 - INDUSTRIAL PRESSURE SENSOR

GS4100C0001AB 2mV/V, 0..1 bar, G1/4, 1M cable IP67

- Suitable for the majority of industrial applications
- Reliable pressure measurement
- · Long service life
- All stainless steel construction



## Product description

The ESI Technology GS4000 is a standard industrial pressure sensor designed to deal with the majority of general industrial applications.

The GS4000 offers a robust yet compact sensor that still offers good performance and is very reliable. The GS4000 starts from -1 - 0 bar up to 0 to 700 bar with a total of eight standard pressure ranges, four options of outputs including 4-20mA and 0-10V and also four different electrical connections including a DIN connector and M12.

## Application examples

- Aerospace
- Power packs
- Mobile hydraulics

## **Specifications**

Ambient temperature-20.85°CApprovalsCE, IECElectrical connection1M Cable outlet screened (IP67)EMCEN61000-6-4, EN61000-6-2Linearity≤±0.4% BSFLMaterials Wetted PartsAluminium oxide, Stainless steel 303, NBRMedia temperature-20.85°COutput2mV/VOverpressure protection1.6 barPressure Range Max1		
Electrical connection  IM Cable outlet screened (IP67)  EMC  EN61000-6-4, EN61000-6-2  Linearity  ≤±0.4% BSFL  Materials Wetted Parts  Aluminium oxide, Stainless steel 303, NBR  Media temperature  -2085°C  Output  2mV/V  Overpressure protection  1.6 bar	Ambient temperature	-2085°C
EMC EN61000-6-4, EN61000-6-2  Linearity ≤±0.4% BSFL  Materials Wetted Parts Aluminium oxide, Stainless steel 303, NBR  Media temperature -2085°C  Output 2mV/V  Overpressure protection 1.6 bar	Approvals	CE, IEC
Linearity ≤±0.4% BSFL   Materials Wetted Parts Aluminium oxide, Stainless steel 303, NBR   Media temperature -2085°C   Output 2mV/V   Overpressure protection 1.6 bar	Electrical connection	1M Cable outlet screened (IP67)
Materials Wetted Parts       Aluminium oxide, Stainless steel 303, NBR         Media temperature       -2085°C         Output       2mV/V         Overpressure protection       1.6 bar	EMC	EN61000-6-4, EN61000-6-2
Media temperature -2085°C  Output 2mV/V  Overpressure protection 1.6 bar	Linearity	≤±0.4% BSFL
Output 2mV/V Overpressure protection 1.6 bar	Materials Wetted Parts	Aluminium oxide, Stainless steel 303, NBR
Overpressure protection 1.6 bar	Media temperature	-2085°C
	Output	2mV/V
Pressure Range Max 1	Overpressure protection	1.6 bar
	Pressure Range Max	1

Pressure Range Min	0
Pressure reference	Gauge or Absolute
Process connection	G1/4
Sensor technology	Cereamic thick film or Bonded foil strain gauge
Storage temperature	540°C
Supply voltage	10 V DC (5-15 V)

