ESI - GS4000 - INDUSTRIAL PRESSURE SENSOR

GS4111CV001AB 0-5Vdc (3 wire), -1..0 bar, G1/4, 1M cable IP67

- Suitable for the majority of industrial applications
- Reliable pressure measurement
- · Long service life
- All stainless steel construction



Product description

The ESI Technology GS4000 is a standard industrial pressure sensor designed to deal with the majority of general industrial applications.

The GS4000 offers a robust yet compact sensor that still offers good performance and is very reliable. The GS4000 starts from -1 - 0 bar up to 0 to 700 bar with a total of eight standard pressure ranges, four options of outputs including 4-20mA and 0-10V and also four different electrical connections including a DIN connector and M12.

Application examples

- Aerospace
- Power packs
- Mobile hydraulics

Specifications

| Ambient temperature-20.85°CApprovalsCE, IECElectrical connection1M Cable outlet screened (IP67)EMCEN61000-6-4, EN61000-6-2Linearity\$\pm\$0.4% BSFLMaterials Wetted PartsAluminium oxide, Stainless steel 303, NBRMedia temperature-20.85°COutput0-5VdcOverpressure protection1.6 barPressure Range Max0 | | |
|--|-------------------------|---|
| Electrical connection IM Cable outlet screened (IP67) EMC EN61000-6-4, EN61000-6-2 Linearity ≤±0.4% BSFL Materials Wetted Parts Aluminium oxide, Stainless steel 303, NBR Media temperature -2085°C Output Overpressure protection 1.6 bar | Ambient temperature | -2085°C |
| EMC EN61000-6-4, EN61000-6-2 Linearity ≤±0.4% BSFL Materials Wetted Parts Aluminium oxide, Stainless steel 303, NBR Media temperature -2085°C Output 0-5Vdc Overpressure protection 1.6 bar | Approvals | CE, IEC |
| Linearity ≤±0.4% BSFL Materials Wetted Parts Aluminium oxide, Stainless steel 303, NBR Media temperature -2085°C Output 0-5Vdc Overpressure protection 1.6 bar | Electrical connection | 1M Cable outlet screened (IP67) |
| Materials Wetted PartsAluminium oxide, Stainless steel 303, NBRMedia temperature-2085°COutput0-5VdcOverpressure protection1.6 bar | EMC | EN61000-6-4, EN61000-6-2 |
| Media temperature -2085°C Output 0-5Vdc Overpressure protection 1.6 bar | Linearity | ≤±0.4% BSFL |
| Output 0-5Vdc Overpressure protection 1.6 bar | Materials Wetted Parts | Aluminium oxide, Stainless steel 303, NBR |
| Overpressure protection 1.6 bar | Media temperature | -2085°C |
| | Output | 0-5Vdc |
| Pressure Range Max 0 | Overpressure protection | 1.6 bar |
| | Pressure Range Max | 0 |

| Pressure Range Min | -1 |
|---------------------|---|
| Pressure reference | Gauge or Absolute |
| | |
| Process connection | G1/4 |
| Sensor technology | Cereamic thick film or Bonded foil strain gauge |
| | |
| Storage temperature | 540°C |
| Supply voltage | 13-30 V DC |

