## ESI - GS4000 - INDUSTRIAL PRESSURE SENSOR

GS4102BV001AB 0-10Vdc (4 wire), -1..0 bar, G1/4, M12

- Suitable for the majority of industrial applications
- Reliable pressure measurement
- · Long service life
- All stainless steel construction



## Product description

The ESI Technology GS4000 is a standard industrial pressure sensor designed to deal with the majority of general industrial applications.

The GS4000 offers a robust yet compact sensor that still offers good performance and is very reliable. The GS4000 starts from -1 - 0 bar up to 0 to 700 bar with a total of eight standard pressure ranges, four options of outputs including 4-20mA and 0-10V and also four different electrical connections including a DIN connector and M12.

## Application examples

- Aerospace
- Power packs
- Mobile hydraulics

## **Specifications**

| Ambient temperature             | -2085°C                                   |
|---------------------------------|-------------------------------------------|
| Approvals                       | CE, IEC                                   |
| Electrical connection           | M12                                       |
| EMC                             | EN61000-6-4, EN61000-6-2                  |
| Linearity                       | ≤±0.4% BSFL                               |
| Materials Wetted Parts          | Aluminium oxide, Stainless steel 303, NBR |
| Media temperature               | -2085°C                                   |
|                                 |                                           |
| Output                          | 0-10Vdc                                   |
| Output  Overpressure protection | 0-10Vdc<br>1.6 bar                        |

| Pressure Range Min  | -1                                              |
|---------------------|-------------------------------------------------|
| Pressure reference  | Gauge or Absolute                               |
|                     |                                                 |
| Process connection  | G1/4                                            |
| Sensor technology   | Cereamic thick film or Bonded foil strain gauge |
|                     |                                                 |
| Storage temperature | 540°C                                           |
| Supply voltage      | 13-30 V DC                                      |

