ESI - GS4000 - INDUSTRIAL PRESSURE SENSOR

GS4112C0.05AB 0-10Vdc (3 wire), 0..0,5 bar, G1/4, 1M cable IP67

- Suitable for the majority of industrial applications
- Reliable pressure measurement
- · Long service life
- All stainless steel construction



Product description

The ESI Technology GS4000 is a standard industrial pressure sensor designed to deal with the majority of general industrial applications.

The GS4000 offers a robust yet compact sensor that still offers good performance and is very reliable. The GS4000 starts from -1 - 0 bar up to 0 to 700 bar with a total of eight standard pressure ranges, four options of outputs including 4-20mA and 0-10V and also four different electrical connections including a DIN connector and M12.

Application examples

- Aerospace
- Power packs
- Mobile hydraulics

Specifications

Ambient temperature-20.85°CApprovalsCE, IECElectrical connection1M Cable outlet screened (IP67)EMCEN61000-6-4, EN61000-6-2Linearity≤±0.4% BSFLMaterials Wetted PartsAluminium oxide, Stainless steel 303, NBRMedia temperature-20.85°COutput0-10VdcOverpressure protection0.8 barPressure Range Max0.5		
Electrical connection EMC EN61000-6-4, EN61000-6-2 Linearity ≤±0.4% BSFL Materials Wetted Parts Aluminium oxide, Stainless steel 303, NBR Media temperature Output Output 0-10Vdc Overpressure protection 1M Cable outlet screened (IP67) EN61000-6-2 4 EN61000-6-2 5 ±0.4% BSFL Aluminium oxide, Stainless steel 303, NBR 0-10Vdc	Ambient temperature	-2085°C
EMC EN61000-6-4, EN61000-6-2 Linearity ≤±0.4% BSFL Materials Wetted Parts Aluminium oxide, Stainless steel 303, NBR Media temperature -2085°C Output 0-10Vdc Overpressure protection 0.8 bar	Approvals	CE, IEC
Linearity ≤±0.4% BSFL Materials Wetted Parts Aluminium oxide, Stainless steel 303, NBR Media temperature -2085°C Output 0-10Vdc Overpressure protection 0.8 bar	Electrical connection	1M Cable outlet screened (IP67)
Materials Wetted Parts Aluminium oxide, Stainless steel 303, NBR Media temperature -2085°C Output 0-10Vdc Overpressure protection 0.8 bar	EMC	EN61000-6-4, EN61000-6-2
Media temperature -2085°C Output 0-10Vdc Overpressure protection 0.8 bar	Linearity	≤±0.4% BSFL
Output 0-10Vdc Overpressure protection 0.8 bar	Materials Wetted Parts	Aluminium oxide, Stainless steel 303, NBR
Overpressure protection 0.8 bar	Media temperature	-2085°C
	Output	0-10Vdc
Pressure Range Max 0.5	Overpressure protection	0.8 bar
	Pressure Range Max	0.5

Pressure Range Min	0
Pressure reference	Gauge or Absolute
Process connection	G1/4
Sensor technology	Cereamic thick film or Bonded foil strain gauge
Storage temperature	540°C
Supply voltage	13-30 V DC

