



# ESI - PR3800 - FLUSH DIAPHRAGM PRESSURE SENSOR

PR3821CV001BJ  
0-5V, -1..0 bar, RJT 38mm female, 1M cable IP67

- Thick film sensor technology for long service life
- Pressure ranges up to 400 bar
- Up to 250°C media temperature option
- Easy clean flush membrane to prevent clogging



## Product description

Robustly constructed from stainless steel, the PR3800 series incorporates the latest strain gauge technology together with a custom IC amplifier offering excellent stability and accuracy over a long service life. The range offers a stable and accurate output signal of 4-20 mA with options for 0-5 V and 0-10 V. Typical applications include food processing, pharmaceutical, petrochemical, waste water and slurry handling. In these installations the process media may corrode the sensing diaphragm or clog the narrow pressure inlet on a standard transmitter. The flush membrane can be easily cleaned for long term reliability and outstanding performance. For hygienic applications the PR3800 series provides a sanitary grade pressure fitting. Seals are available in a variety of forms and materials for a wide range of applications and can be directly attached to the proposed connection or remotely via stainless steel capillary. Pressure ranges available from 0-200 mbar to

An optional ATEX and IECEx approved versions of this range are available for explosion protection for flammable gases (zone 0), dusts (zone 20) and mining areas (group I M1).

## Specifications

Ambient temperature	-20..85°C
Electrical connection	1M Cable outlet screened (IP67)
EMC	EN61000-6-4, EN61000-6-2
Linearity	≤±0.3% BSFL
Materials Wetted Parts	Stainless steel
Media temperature	-20..85°C
Output	0-5V
Overpressure protection	2 bar
Pressure Range Max	0
Pressure Range Min	-1

<b>Pressure reference</b>	Gauge
<b>Process connection</b>	RJT 38mm female
<b>Sensor technology</b>	Ceramic thick film or Isolated Piezoresistive Silicon
<b>Storage temperature</b>	5..40°C
<b>Supply voltage</b>	13-30 V DC