



ESI - PR3800 - FLUSH DIAPHRAGM PRESSURE SENSOR

PR3822CV001BV
0-10V, -1..0 bar, SMS 40mm female, 1M cable IP67

- Thick film sensor technology for long service life
- Pressure ranges up to 400 bar
- Up to 250°C media temperature option
- Easy clean flush membrane to prevent clogging



Product description

Robustly constructed from stainless steel, the PR3800 series incorporates the latest strain gauge technology together with a custom IC amplifier offering excellent stability and accuracy over a long service life. The range offers a stable and accurate output signal of 4-20 mA with options for 0-5 V and 0-10 V. Typical applications include food processing, pharmaceutical, petrochemical, waste water and slurry handling. In these installations the process media may corrode the sensing diaphragm or clog the narrow pressure inlet on a standard transmitter. The flush membrane can be easily cleaned for long term reliability and outstanding performance. For hygienic applications the PR3800 series provides a sanitary grade pressure fitting. Seals are available in a variety of forms and materials for a wide range of applications and can be directly attached to the proposed connection or remotely via stainless steel capillary. Pressure ranges available from 0-200 mbar to

An optional ATEX and IECEx approved versions of this range are available for explosion protection for flammable gases (zone 0), dusts (zone 20) and mining areas (group I M1).

Specifications

| | |
|-------------------------|---------------------------------|
| Ambient temperature | -20..85°C |
| Electrical connection | 1M Cable outlet screened (IP67) |
| EMC | EN61000-6-4, EN61000-6-2 |
| Linearity | ≤±0.3% BSFL |
| Materials Wetted Parts | Stainless steel |
| Media temperature | -20..85°C |
| Output | 0-10V |
| Overpressure protection | 2 bar |
| Pressure Range Max | 0 |
| Pressure Range Min | -1 |

| | |
|----------------------------|---|
| Pressure reference | Gauge |
| Process connection | SMS 40mm |
| Sensor technology | Ceramic thick film or Isolated Piezoresistive Silicon |
| Storage temperature | 5..40°C |
| Supply voltage | 13-30 V DC |