



APLISENS - APRE-2000G SMART DIFFERENTIAL PRESSURE SENSORS

APRE-2000G

Please see below for available options and technical data

- Pressure range -100 mbar to 100 mbar
- Min range 0.2mbar
- Three body styles available
- ATEX version



Product description

The Aplisens APRE-2000G Smart differential pressure transmitter is applicable to gases, to the measurements of their pressure, underpressure and differential pressure.

The ability to select the radical conversion characteristics also enables this differential pressure transmitter to be used in gas flow measurement systems using reduced pipes or other impeding elements.

The APRE-2000G Smart uses HART protocol and the following metrological parameters can be configured through this:

- Units of pressure
- Start and end-points of the set range
- Damping time constant
- Conversion characteristics (radical, inversion, user's non-linear characteristics)

And through the data interchange with the probe you can also:


- Identify the transmitter
- Read the currently measured hydrostatic pressure value, output current and percentage of measuring range

This smart differential pressure transmitter has an accuracy of 0.1%, with five standard measuring ranges to choose from and is also available in ATEX.

Application examples:

- Blast pressure
- Chimney draughts
- Furnace chambers
- Clean rooms

Please refer to the image below for ordering information.

Model	Code		Description	
APRE-2000G			Smart differential pressure transmitter	
Certificates	/Exia.....		 II 1/2G Ex ia IIC T4/T5 Ga/Gb II 1 D Ex ia IIC T110°C Da I M1 Ex ia I Ma	
Casing, output signal	/PD..... /PZ..... /N.....		Housing IP65 with DIN43650 connector, without display, output 4-20mA + Hart 304SS housing, IP66, without display, output 4-20mA + Hart Housing IP65, electrical connector PG-7 (ATEX version not available)	
Nominal measuring range	/0÷25 mbar.....		Range 0÷25 mbar (0÷2500 Pa)	Min. set range 1mbar (100 Pa)
	/-2,5÷2,5 mbar.....		-2.5÷2.5mbar (250÷250 Pa)	0,2 mbar (20 Pa)
	/-7÷7 mbar.....		-7÷7 mbar (700÷700 Pa)	1mbar (100 Pa)
	/-25÷25 mbar.....		-25÷25 mbar (2500÷2500 Pa)	5mbar (500 Pa)
	/-100÷100 mbar.....		-100÷100mbar (10÷10 kPa)	20mbar (2 kPa)
	Measuring set range		/...+... [required units]	
Process connections	/PCV.....		Process connection with terminal connecting for Ø6mm elastic pipe. Mounting bracket for wall mounting is a standard.	
	/C.....		Thread 1/4 NPT F on cover flange. Material of cover flange 304ss. Allows mounting with a valve manifold.	
Accessories	/M20x1,5/Ø6.....		Adapter from Ø 6mm elastic pipe for M20x1,5 M thread (only version with PCV process connection)	
	/RedSpaw C.....		Connector to weld impulse pipes dia. 12 and 14 mm, material 15HM. (only version with process connection C type)	
	/+VM-3/A.....		Assembled with a 3-way valve manifold (further specification of manifold - see data sheet) . Only version with C type process connection.	
	/+VM-5/A.....		Assembled with a 5-way valve manifold (further specification of manifold - see data sheet) . Only version with C type process connection.	
Other specification	/.....		Description of required parameters	

;

Specifications

Approvals	ATEX
Connection Thread	M20x1.5, Hose connection 6 mm, 1/4 NPT
IP Class	IP65, IP66, IP67
Material	Stainless steel AISI 304
Materials Wetted Parts	Stainless steel AISI 304
Pressure range max	100
Pressure range min	-100
Signal type	4-20 mA / Hart
Supply Voltage DC Max	36
Supply Voltage DC Min	7.5
Temperature range of media from	-10
Temperature range of media to	70