



SUCO 0675/0680/0690 PRESSURE SENSOR

Robust Series

0690600411013
0..6 bar, 4-20mA, G1/4", DIN-A

- For low pressures & vacuum
- Long life time even under high pressure change rates
- Excellent media compatibility
- Oil filled measuring cell



Product description

The Suco robust series of pressure sensors offers an option for vacuum applications with good overpressure protection (up to 3x), long service life even under high pressure change rates whilst giving very low temperature error and excellent long-term stability. Using a highly sensitive piezo-resistive sensor in a fluorine oil filled measuring cell for a high accuracy and repeatability, there are eight standard pressure ranges starting at -1-0 bar (vacuum) all the way up to 0-100 bar, with three output signal options of 0.5-4.5V, 0-10V and 4-20mA. The wetted parts are made of stainless steel (AISI 316L & AISI 316L) and NBR or FKM giving excellent media compatibility with four standard electrical connection options including Pre-cabled, DIN and M12 combined with one standard thread type.

The 0675 range with 0.5-4.5v Ratiometric are also available on request

Application examples

- Agricultural
- Chemical
- Hydrogen
- Medical
- Mobile hydraulics
- Off highway
- Off-shore
- Oxygen
- Process
- Rail
- Seawater
- Vacuum

Specifications

| | |
|-----------------------|----------------------|
| Connection Thread | G1/4-E |
| Electrical connection | DIN EN 175301-803-A |
| IP Class | IP65 |
| Material of body | Stainless steel 316L |

| | |
|---------------------------------|----------------------|
| Materials Wetted Parts | Stainless steel 316L |
| Pressure Range Max | 6 |
| Pressure Range Min | 0 |
| Pressure type | Relative |
| Response Time | 2 |
| Signal type | 4-20 mA |
| Supply Voltage DC Max | 32 |
| Supply Voltage DC Min | 10 |
| Temperature ambient from | -40 |
| Temperature ambient to | 100 |
| Temperature range of media from | -40 |
| Temperature range of media to | 100 |
| Weight | 80 |