SUCO - 0705/0710/0720 PRESSURE SENSOR

High performance series

071016141B002 0-10V, 0..16 bar, G1/4-E, M12

- Measuring range up to 600 bar
- Silicon-on-sapphire sensor
- Outstanding overpressure protection
- Outstanding repeatability





Product description

The SUCO 0705/0710/0720 high performance series pressure sensor is an advanced pressure monitoring solution with unrivalled attributes. Offering ten standard pressure ranges with options of six different electrical connectors a thread of G1/4 (eight available in total) and 0.5-4.5 V ratiomateric, 0-10V or 4-20mA outputs. The 07 series uses silicon-on-sapphire technology in a titanium all welded design offering outstanding overpressure protection, media compatibility and the highest repeatability.


Common applications include mobile hydraulics, off-shore/marine, high pressure systems and more.

Specifications

Accuracy	±0.5% FS
Burst Pressure	128

Connection Thread	G1/4-E	
Electrical connection	M12x1 4-pole	
IP Class	IP67	
Long-Term Stability	±0.1% FS p.a.	
Material of body	Stainless steel 1.4305	
Materials Wetted Parts	Stainless steel 1.4305, Titanium	
Overpressure protection	64 bar	
Pressure Range Max	16	
Pressure Range Min	0	
Pressure reference	Gauge	
Pressure rise	5 bar/ms	
Repeatability & Reproducibility	±0.1% FS	
Response Time	2	
Shock Resistance	500m / s²; 11 ms half sine wave; DIN EN 60068-2-27	
Signal type	0-10 V	
Supply Voltage DC Max	32	
Supply Voltage DC Min	12	
Temperature ambient from	-40	
Temperature ambient to	100	
Temperature error	±0.01% FS/°C	
Temperature range of media from	-40	
Temperature range of media to	125	
Weight	80	

20g: 4..2000 Hz sine wave, DIN EN 60068-2-6



Vibration Resistance

Pin 1	Uv+
Pin 2	nc
Pin 3	Gnd
Pin 4	Out



