SUCO - 0705/0710/0720 PRESSURE SENSOR

High performance series

072025241B002 4-20mA, 0..250 bar, G1/4-E, M12

- Measuring range up to 600 bar
- Silicon-on-sapphire sensor
- Outstanding overpressure protection
- Outstanding repeatability





Product description

The SUCO 0705/0710/0720 high performance series pressure sensor is an advanced pressure monitoring solution with unrivalled attributes. Offering ten standard pressure ranges with options of six different electrical connectors a thread of G1/4 (eight available in total) and 0.5-4.5 V ratiomateric, 0-10V or 4-20mA outputs. The 07 series uses silicon-on-sapphire technology in a titanium all welded design offering outstanding overpressure protection, media compatibility and the highest repeatability.

Common applications include mobile hydraulics, off-shore/marine, high pressure systems and more.

Specifications


Accuracy

±0.5% FS

Burst Pressure

2000

| Connection Thread | G1/4-E | | |
|---------------------------------|---|--|--|
| Electrical connection | M12x1 4-pole | | |
| | · | | |
| IP Class | IP67 | | |
| Long-Term Stability | ±0.1% FS p.a. | | |
| Material of body | Stainless steel 1.4305 | | |
| Materials Wetted Parts | Stainless steel 1.4305, Titanium | | |
| Overpressure protection | 1000 bar | | |
| Pressure Range Max | 250 | | |
| Pressure Range Min | 0 | | |
| Pressure reference | Gauge | | |
| Pressure rise | 5 bar/ms | | |
| Pressure type | Relative | | |
| Repeatability & Reproducibility | ±0.1% FS | | |
| Response Time | 2 | | |
| Shock Resistance | 500m / s ² ; 11 ms half sine wave; DIN EN 60068-2-27 | | |
| Signal type | 4-20 mA | | |
| Supply Voltage DC Max | 32 | | |
| Supply Voltage DC Min | 10 | | |
| Temperature ambient from | -40 | | |
| Temperature ambient to | 100 | | |
| Temperature error | ±0.01% FS/°C | | |
| Temperature range of media from | -40 | | |
| Temperature range of media to | 125 | | |
| Weight | 80 | | |
| Vibration Resistance | 20g: 42000 Hz sine wave, DIN EN 60068-2-6 | | |





| Sealing G 1/4 DN EN ISO 1179-2 (DN 352-11) form E | G1/4 DIN 3852-A | | ST NPT 1/4 |
|--|--------------------|-----------------|--|
| Thread code: 41 | Thread code: 03 | Thread code: 04 | Thread code: 09 |
| M 10x1 DIN 3552-A | 7/16-20 UNF | 9/16-18 UNF | Circle And |
| Thread code: 30 | Thread code: 20 | Thread code: 21 | Thread code: 42 |



