



## SUCO - 0116/0117 PRESSURE SWITCH

IP67, IP6K9K

0117420281604

50..150 bar, G1/8, Nc, NBR, Deutsch DT04-3P

- Up to 42 V
- Deutsch DT04-3P integrated connector
- Six adjustment ranges from 0,1..1 bar to 50..150 bar
- Normally open or normally closed
- Overpressure safety of 300 bar or 600 bar



### Product description

The 0116/0117 series pressure switch is part of the integrated connector range from SUCO offering high IP rating. Integrated Deutsch DT04-3P connector and a maximum voltage of 42V with normally open or normally closed contacts housed in a hex 24 zinc plated body offering a high pressure resistance. The switch point is very stable even after a long period of time and high load and is also adjustable on site and can come pre-set.

Common applications include automotive, mobile hydraulics, water applications and braking systems.

### Specifications

<b>Adjustment range max</b>	150
<b>Adjustment range min</b>	50
<b>Approvals</b>	CSA US, RoHS II
<b>Contact Rating Max</b>	4
<b>Deviation max</b>	±5
<b>Electrical connection</b>	Deutsch DT04-3P
<b>Function</b>	Normally Closed (SPST)
<b>IP Class</b>	IP67, IP6K9K
<b>Material of body</b>	Zinc-plated steel
<b>Materials Wetted Parts</b>	Zinc-plated steel, NBR
<b>Max switching frequency/min</b>	200
<b>Max. pressure</b>	600

Membrane Material	NBR
Process connection	1/8 BSP
Temperature ambient from	-20
Temperature ambient to	80
Temperature range of media from	-40
Temperature range of media to	100
Weight	90
Voltage AC / DC Max	42
Voltage AC / DC Min	10



