SUCO - 0705/0710/0720 PRESSURE SENSOR

High performance series

072010141B001 4-20mA, 0..10 bar, G1/4-E, DIN

- Measuring range up to 600 bar
- Silicon-on-sapphire sensor
- Outstanding overpressure protection
- Outstanding repeatability





Product description

The SUCO 0705/0710/0720 high performance series pressure sensor is an advanced pressure monitoring solution with unrivalled attributes. Offering ten standard pressure ranges with options of six different electrical connectors a thread of G1/4 (eight available in total) and 0.5-4.5 V ratiomateric, 0-10V or 4-20mA outputs. The 07 series uses silicon-on-sapphire technology in a titanium all welded design offering outstanding overpressure protection, media compatibility and the highest repeatability.

Common applications include mobile hydraulics, off-shore/marine, high pressure systems and more.

Specifications

±0.5% FS


Burst Pressure

80

Connection Thread	G1/4-E		
Electrical connection	DIN EN 175301-803-A		
IP Class	IP67		
Long-Term Stability	±0.1% FS p.a.		
Material of body	Stainless steel 1.4305		
Materials Wetted Parts	Stainless steel 1.4305, Titanium		
Overpressure protection	40 bar		
Pressure Range Max	10		
Pressure Range Min	0		
Pressure reference	Gauge		
Pressure rise	5 bar/ms		
Repeatability & Reproducibility	±0.1% FS		
Response Time	2		
Shock Resistance	500m / s²; 11 ms half sine wave; DIN EN 60068-2-27		
Signal type	4-20 mA		
Supply Voltage DC Max	32		
Supply Voltage DC Min	10		
Temperature ambient from	-40		
Temperature ambient to	100		
Temperature error	±0.01% FS/°C		
Temperature range of media from	-40		
Temperature range of media to	125		
Weight	80		
Vibration Resistance	20g: 42000 Hz sine wave, DIN EN 60068-2-6		

Vibration Resistance

20g: 4..2000 Hz sine wave, DIN EN 60068-2-6





Sealing G 1/4 DN EN ISO 1179-2 (DN 352-11) form E	G1/4 DIN 3852-A		ST NPT 1/4
Thread code: 41	Thread code: 03	Thread code: 04	Thread code: 09
M 10x1 DIN 3552-A	7/16-20 UNF	9/16-18 UNF	Circle And
Thread code: 30	Thread code: 20	Thread code: 21	Thread code: 42



