## SUCO - 0705/0710/0720 PRESSURE SENSOR

High performance series

071040241B001 0-10V, 0..400 bar, G1/4-E, DIN

- Measuring range up to 600 bar
- Silicon-on-sapphire sensor
- Outstanding overpressure protection
- Outstanding repeatability





## Product description

The SUCO 0705/0710/0720 high performance series pressure sensor is an advanced pressure monitoring solution with unrivalled attributes. Offering ten standard pressure ranges with options of six different electrical connectors a thread of G1/4 (eight available in total) and 0.5-4.5 V ratiomateric, 0-10V or 4-20mA outputs. The 07 series uses silicon-on-sapphire technology in a titanium all welded design offering outstanding overpressure protection, media compatibility and the highest repeatability.


Common applications include mobile hydraulics, off-shore/marine, high pressure systems and more.

## Specifications

| Accuracy       | ±0.5% FS |
|----------------|----------|
| Burst Pressure | 2000     |

| Connection Thread               | G1/4-E   |
|---------------------------------|--|
| Electrical connection           | DIN EN 175301-803-A                                |
| IP Class                        | IP67   |
| Long-Term Stability             | ±0.1% FS p.a.                                      |
| Material of body                | Stainless steel 1.4305                             |
| Materials Wetted Parts          | Stainless steel 1.4305, Titanium                   |
| Overpressure protection         | 1600 bar   |
| Pressure Range Max              | 400  |
| Pressure Range Min              | 0  |
| Pressure reference              | Gauge  |
| Pressure rise                   | 5 bar/ms   |
| Repeatability & Reproducibility | ±0.1% FS   |
| Response Time                   | 2  |
| Shock Resistance                | 500m / s²; 11 ms half sine wave; DIN EN 60068-2-27 |
| Signal type                     | 0-10 V   |
| Supply Voltage DC Max           | 32   |
| Supply Voltage DC Min           | 12   |
| Temperature ambient from        | -40  |
| Temperature ambient to          | 100  |
| Temperature error               | ±0.01% FS/°C                                       |
| Temperature range of media from | -40  |
| Temperature range of media to   | 125  |
| Weight                          | 80   |
|                                 |  |

20g: 4..2000 Hz sine wave, DIN EN 60068-2-6



Vibration Resistance



