



SUCO - 0110/0111 PRESSURE SWITCH

IP67, IP6K9K

0110404033015

0,1..1 bar, G1/4, Nc, FKM, Deutsch DT04-2P

- Up to 42 V
- Deutsch DT04-2P integrated connector
- Six adjustment ranges from 0,1..1 bar to 50..150 bar
- Normally open or normally closed
- Overpressure safety of 300 bar or 600 bar



Product description

The 0110/0111 series pressure switch is part of the integrated connector range from SUCO offering high IP rating. Integrated Deutsch DT04-2P connector and a maximum voltage of 42V with normally open or normally closed contacts housed in a hex 24 zinc plated body offering a high pressure resistance. The switch point is very stable even after a long period of time and high load and is also adjustable on site and can come pre-set.

Common applications include automotive, mobile hydraulics, water applications and braking systems.

Specifications

Adjustment range max	1
Adjustment range min	0.1
Approvals	CSA US, RoHS II
Contact Rating Max	4
Deviation max	±0,2
Electrical connection	2-pole Deutsch
Function	Normally Closed (SPST)
IP Class	IP67, IP6K9K
Material of body	Zinc-plated steel
Materials Wetted Parts	FKM, Zinc-plated steel
Max switching frequency/min	200
Max. pressure	300
Membrane Material	FKM

Process connection	1/4 BSP
Temperature ambient from	-20
Temperature ambient to	80
Temperature range of media from	-5
Temperature range of media to	120
Weight	90
Voltage AC / DC Max	42
Voltage AC / DC Min	10

