



## SUCO - 0159 PRESSURE SWITCH

### Aluminium body

0159428142001

1..10 bar, G1/4 female, CO, EPDM, PG9, Aluminium

- Up to 250 V
- Pg9 Cable gland
- Eight adjustment ranges from 0,2..2 bar to 40..400 bar
- Changeover (SPDT)
- Over pressure safety from 200 bar up to 600 bar



#### Product description

The 0159 series pressure switch is part of the heavy duty range from SUCO offering adjustment while in operation. Pg9 cable gland connector and a maximum voltage of 250 V with a normally open and normally closed contact housed in a 30 A/F aluminium body offering a high pressure resistance. The switch point is very stable even after a long period of time and high load and can come pre-set.

Common applications include factory environments, processes requiring constant monitoring and general hydraulic applications.

#### Specifications

<b>Adjustment range max</b>	10
<b>Adjustment range min</b>	1
<b>Approvals</b>	CE, RoHS II
<b>Contact load max ac</b>	2.5
<b>Contact load max dc</b>	0.3
<b>Deviation max</b>	±0,5
<b>Electrical connection</b>	Cable PG9
<b>Function</b>	Changeover (SPDT)
<b>IP Class</b>	IP65
<b>Material of body</b>	Aluminium
<b>Materials Wetted Parts</b>	Aluminium, EPDM
<b>Max switching frequency/min</b>	200

Max. pressure	200
Membrane Material	EPDM
Process connection	G1/4 female
Temperature ambient from	-20
Temperature ambient to	80
Temperature range of media from	-30
Temperature range of media to	120
Weight	240
Voltage AC / DC Max	250

