INSULATED FERRULES ON REEL

V30MA000030
2.5mm² x 8mm Ferrule - Blue (Reel 3000)



- Tin-plated copper for strong conductivity.
- No need to change tools or machines.
- Ideal for high-speed automated crimping.
- Sizes: 0.34–2.5 mm², 8–10 mm length.
- Gas-tight, vibration-proof crimps.

PRODUCT DESCRIPTION

Z+F Ferrules on Reel are designed to make wire termination fast, neat, and reliable – ideal for use in automated production environments. These ferrules suit wire sizes from 0.34 to 2.5 mm² (AWG 22–14) and are made from high-quality tin-plated copper with a durable plastic collar. They fully comply with DIN 46228 Part 4 standards, ensuring consistent performance and safety.

SPECIFICATIONS

Color	Blue
Country of origin	DE
Cross Section Max	2.5
Diameter of collar	4.2
Diameter of tube	2.2
DIN 46228-1:1992	No
DIN 46228-4:1990	Yes
Length	15
Length of tube	8
Operating temperature from	-5
Operating temperature to	105
Pack Size	1
Rated wire cross section to (AWG)	14
Stripping Length	10
Tariff code	85369010

Thickness of collar	0.25
Thickness of tube	0.15
Weight	0.22

