


INSULATED BOOTLACE FERRULES 0.14MM² TO 4MM²

V30AE004154

0.25mm² x 12mm Ferrule -Violet

- Funnel feed-in made of polypropylene
- Heat resistant up to 120 °C
- For wires from 0.14...4 mm²
- Material: E-Cu/A-Cu, galvanically tin-plated





Product description

European manufactured, this range ensures a reliable crimp without splitting.

Specifications

Color	Light blue
Conductor tube	Copper alloy
Contact surface	Galvanic tin-plated, shiny
Country of origin	DE
Cross Section Max	0.25
Diameter of collar	1.8
Diameter of tube	0.85
DIN 46228-1:1992	No
DIN 46228-4:1990	Yes
Length	16
Length of tube	12
Operating temperature from	-5
Operating temperature to	105
Pack Size	500

Plastic collar	Polypropylene-homopolymer
Rated wire cross section to (AWG)	24
Standard	French Standard
Stripping Length	14
Tariff code	85369010
Thickness of collar	0.25
Thickness of tube	0.15
Weight	0.06



Bearbeitung Description	AWG	Teilcode/Teil-Nr. Cable code/Cable no.	DN	RDS	L	L ₂	L ₁	S ₁	S ₂	S ₃	VPE
0.14 8 N 25	V30AE000907	V30AE000909	10	6	0.6	0.15	1.5	0.25	500		
0.14 8 L 25	V30AE000908	V30AE000901	12	8	0.6	0.15	1.5	0.25	500		
0.25 8 N 24	V30AE000001	V30AE000002	10	6	0.85	0.15	1.8	0.25	500		
		V30AE000044									
0.25 8 L 24	V30AE000002	V30AE000003	12	8	0.85	0.15	1.8	0.25	500		
		V30AE000045									
0.25 12 L3 24	V30AE000485	V30AE000486	16	12	0.65	0.15	1.8	0.25	500		
		V30AE000004									
0.34 8 N 22	V30AE000003	V30AE000005	10	6	0.85	0.15	2	0.25	500		
		V30AE000006									
0.34 8 L 22	V30AE000004	V30AE000007	12	8	0.85	0.15	2	0.25	500		
		V30AE000008									
0.34 12 L3 22	V30AE000486	V30AE000487	16	12	0.65	0.15	2	0.25	500		
0.5 8 K 20	V30AE000005	V30AE000007	12	6	1	0.15	2.8	0.25	500		
0.5 8 N 20	V30AE000005	V30AE000008	14	8	1	0.15	2.8	0.25	500		
0.5 10 HL 20	V30AE000007	V30AE000009	16	10	1	0.15	2.8	0.25	500		
0.5 12 L 20	V30AE000486	V30AE000488	16	12	1	0.15	2.8	0.25	500		
0.75 8 N 18	V30AE000008	V30AE000040	12	8	1.2	0.15	2.8	0.25	500		
0.75 8 N 18	V30AE000009	V30AE000041	14	8	1.2	0.15	2.8	0.25	500		
0.75 9 H4S 18	V30AE000007	V30AE000009	16	9	1.2	0.15	2.8	0.25	500		
0.75 10 HL 18	V30AE000010	V30AE000042	16	10	1.2	0.15	2.8	0.25	500		
0.75 12 L 18	V30AE000011	V30AE000043	16	12	1.2	0.15	2.8	0.25	500		
1 8 K 15	V30AE000012	V30AE000044	12	6	1.4	0.15	3	0.25	500		
1 8 N 15	V30AE000013	V30AE000045	14	8	1.4	0.15	3	0.25	500		
1 10 HL 15	V30AE000014	V30AE000046	16	10	1.4	0.15	3	0.25	500		
1 12 L 15	V30AE000015	V30AE000047	16	12	1.4	0.15	3	0.25	500		
1.5 8 K 15	V30AE000016	V30AE000048	12	6	1.7	0.15	3.5	0.25	500		
1.5 8 N 15	V30AE000017	V30AE000049	14	8	1.7	0.15	3.5	0.25	500		
1.5 10 HL 15	V30AE000018	V30AE000050	16	10	1.7	0.15	3.5	0.25	500		

Bearbeitung Description	AWG	Teilcode/Teil-Nr. Cable code/Cable no.	DN	RDS	L	L ₂	L ₁	S ₁	S ₂	S ₃	VPE
0.14 8 N 25	V30AE000907	V30AE000909	10	6	0.6	0.15	1.5	0.25	500		
0.14 8 L 25	V30AE000908	V30AE000901	12	8	0.6	0.15	1.5	0.25	500		
0.25 8 N 24	V30AE000001	V30AE000002	10	6	0.85	0.15	1.8	0.25	500		
		V30AE000044									
0.25 8 L 24	V30AE000002	V30AE000003	12	8	0.85	0.15	1.8	0.25	500		
		V30AE000045									
0.25 12 L3 24	V30AE000485	V30AE000486	16	12	0.65	0.15	1.8	0.25	500		
		V30AE000004									
0.34 8 N 22	V30AE000003	V30AE000005	10	6	0.85	0.15	2	0.25	500		
		V30AE000006									
0.34 8 L 22	V30AE000004	V30AE000007	12	8	0.85	0.15	2	0.25	500		
		V30AE000008									
0.34 12 L3 22	V30AE000486	V30AE000487	16	12	0.65	0.15	2	0.25	500		
0.5 8 K 20	V30AE000005	V30AE000007	12	6	1	0.15	2.8	0.25	500		
0.5 8 N 20	V30AE000005	V30AE000008	14	8	1	0.15	2.8	0.25	500		
0.5 10 HL 20	V30AE000007	V30AE000009	16	10	1	0.15	2.8	0.25	500		
0.5 12 L 20	V30AE000486	V30AE000488	16	12	1	0.15	2.8	0.25	500		
0.75 8 N 18	V30AE000008	V30AE000040	12	8	1.2	0.15	2.8	0.25	500		
0.75 8 N 18	V30AE000009	V30AE000041	14	8	1.2	0.15	2.8	0.25	500		
0.75 9 H4S 18	V30AE000007	V30AE000009	16	9	1.2	0.15	2.8	0.25	500		
0.75 10 HL 18	V30AE000010	V30AE000042	16	10	1.2	0.15	2.8	0.25	500		
0.75 12 L 18	V30AE000011	V30AE000043	16	12	1.2	0.15	2.8	0.25	500		
1 8 K 15	V30AE000012	V30AE000044	12	6	1.4	0.15	3	0.25	500		
1 8 N 15	V30AE000013	V30AE000045	14	8	1.4	0.15	3	0.25	500		
1 10 HL 15	V30AE000014	V30AE000046	16	10	1.4	0.15	3	0.25	500		
1 12 L 15	V30AE000015	V30AE000047	16	12	1.4	0.15	3	0.25	500		
1.5 8 K 15	V30AE000016	V30AE000048	12	6	1.7	0.15	3.5	0.25	500		
1.5 8 N 15	V30AE000017	V30AE000049	14	8	1.7	0.15	3.5	0.25	500		
1.5 10 HL 15	V30AE000018	V30AE000050	16	10	1.7	0.15	3.5	0.25	500		