


INSULATED BOOTLACE FERRULES 0.14MM² TO 4MM²

V30AE000003

Ferrules 0.34-6 Green (500-Pack)

- Funnel feed-in made of polypropylene
- Heat resistant up to 120 °C
- For wires from 0.14...4 mm²
- Material: E-Cu/A-Cu, galvanically tin-plated





PRODUCT DESCRIPTION

European manufactured, this range ensures a reliable crimp without splitting.

SPECIFICATIONS

Color	Turquoise
Country of origin	DE
Cross Section Max	0.34
Diameter of collar	2
Diameter of tube	0.85
DIN 46228-1:1992	No
DIN 46228-4:1990	Yes
Length	10
Length of tube	6
Operating temperature from	-5
Operating temperature to	105
Pack Size	500
Rated wire cross section to (AWG)	22
Standard	German Standard
Stripping Length	8
Tariff code	85369010

Thickness of collar	0.25
Thickness of tube	0.15
Weight	0.06



Bezeichnung Description	AWG	Fitzcock/Bentley Colour code/Color (in)			Finnrade mm Dimensions (mm)					Stück Pieces	
		ZUF	DN	RDS	L	L ₁	L ₂	S ₁	S ₂		VPE
0.14 B N 24	V30AE000007				10	6	0.6	0.15	1.8	0.25	500
0.14 B L 26	V30AE000008				12	8	0.6	0.15	1.8	0.25	500
0.25 B N 24	V30AE000001				10	6	0.85	0.15	1.8	0.25	500
0.25 B L 24	V30AE000002				12	8	0.85	0.15	1.8	0.25	500
0.25 L2 L3 24	V30AE004185				16	12	0.65	0.15	1.8	0.25	500
0.34 B N 22	V30AE000003				10	6	0.65	0.15	2	0.25	500
0.34 B L 22	V30AE000004				12	8	0.65	0.15	2	0.25	500
0.34 L2 L3 22	V30AE004186				16	12	0.65	0.15	2	0.25	500
0.5 B K 20	V30AE000005	V30AE000007	V30AE000007		12	8	1	0.15	2.6	0.25	500
0.5 B N 20	V30AE000005	V30AE000008	V30AE000008		14	8	1	0.15	2.6	0.25	500
0.5 N3 HL 20	V30AE000007	V30AE000009	V30AE000009		16	10	1	0.15	2.6	0.25	500
0.5 L2 L 20	V30AE004186	V30AE004186	V30AE004186		16	12	1	0.15	2.6	0.25	500
0.75 B N 18	V30AE000008	V30AE000010	V30AE000010		12	8	1.2	0.15	2.8	0.25	500
0.75 B N 18	V30AE000009	V30AE000011	V30AE000011		14	8	1.2	0.15	2.8	0.25	500
0.75 B H4S 18	V30AE000007	V30AE000008	V30AE000008		16	12	1.2	0.15	2.8	0.25	500
0.75 N3 HL 18	V30AE000010	V30AE000012	V30AE000012		16	12	1.2	0.15	2.8	0.25	500
0.75 L2 L 18	V30AE000011	V30AE000013	V30AE000013		16	12	1.2	0.15	2.8	0.25	500
1 B K 16	V30AE000012	V30AE000014	V30AE000014		12	8	1.4	0.15	3	0.25	500
1 B N 16	V30AE000013	V30AE000015	V30AE000015		14	8	1.4	0.15	3	0.25	500
1 N3 HL 16	V30AE000014	V30AE000016	V30AE000016		16	10	1.4	0.15	3	0.25	500
1 L2 L 16	V30AE000015	V30AE000017	V30AE000017		16	12	1.4	0.15	3	0.25	500
1.5 B K 16	V30AE000016	V30AE000018	V30AE000018		12	8	1.7	0.15	3.5	0.25	500
1.5 B N 16	V30AE000017	V30AE000019	V30AE000019		14	8	1.7	0.15	3.5	0.25	500
1.5 N3 HL 16	V30AE000018	V30AE000020	V30AE000020		16	10	1.7	0.15	3.5	0.25	500

Bezeichnung Description	AWG	Fitzcock/Bentley Colour code/Color (in)			Finnrade mm Dimensions (mm)					Stück Pieces	
		ZUF	DN	RDS	L	L ₁	L ₂	S ₁	S ₂		VPE
0.14 B N 24	V30AE000007				10	6	0.6	0.15	1.8	0.25	500
0.14 B L 26	V30AE000008				12	8	0.6	0.15	1.8	0.25	500
0.25 B N 24	V30AE000001				10	6	0.85	0.15	1.8	0.25	500
0.25 B L 24	V30AE000002				12	8	0.85	0.15	1.8	0.25	500
0.25 L2 L3 24	V30AE004185				16	12	0.65	0.15	1.8	0.25	500
0.34 B N 22	V30AE000003				10	6	0.65	0.15	2	0.25	500
0.34 B L 22	V30AE000004				12	8	0.65	0.15	2	0.25	500
0.34 L2 L3 22	V30AE004186				16	12	0.65	0.15	2	0.25	500
0.5 B K 20	V30AE000005	V30AE000007	V30AE000007		12	8	1	0.15	2.6	0.25	500
0.5 B N 20	V30AE000005	V30AE000008	V30AE000008		14	8	1	0.15	2.6	0.25	500
0.5 N3 HL 20	V30AE000007	V30AE000009	V30AE000009		16	10	1	0.15	2.6	0.25	500
0.5 L2 L 20	V30AE004186	V30AE004186	V30AE004186		16	12	1	0.15	2.6	0.25	500
0.75 B N 18	V30AE000008	V30AE000010	V30AE000010		12	8	1.2	0.15	2.8	0.25	500
0.75 B N 18	V30AE000009	V30AE000011	V30AE000011		14	8	1.2	0.15	2.8	0.25	500
0.75 B H4S 18	V30AE000007	V30AE000008	V30AE000008		16	12	1.2	0.15	2.8	0.25	500
0.75 N3 HL 18	V30AE000010	V30AE000012	V30AE000012		16	12	1.2	0.15	2.8	0.25	500
0.75 L2 L 18	V30AE000011	V30AE000013	V30AE000013		16	12	1.2	0.15	2.8	0.25	500
1 B K 16	V30AE000012	V30AE000014	V30AE000014		12	8	1.4	0.15	3	0.25	500
1 B N 16	V30AE000013	V30AE000015	V30AE000015		14	8	1.4	0.15	3	0.25	500
1 N3 HL 16	V30AE000014	V30AE000016	V30AE000016		16	10	1.4	0.15	3	0.25	500
1 L2 L 16	V30AE000015	V30AE000017	V30AE000017		16	12	1.4	0.15	3	0.25	500
1.5 B K 16	V30AE000016	V30AE000018	V30AE000018		12	8	1.7	0.15	3.5	0.25	500
1.5 B N 16	V30AE000017	V30AE000019	V30AE000019		14	8	1.7	0.15	3.5	0.25	500
1.5 N3 HL 16	V30AE000018	V30AE000020	V30AE000020		16	10	1.7	0.15	3.5	0.25	500