


# INSULATED BOOTLACE FERRULES

## 0.14MM<sup>2</sup> TO 4MM<sup>2</sup>

V30AE000005

0.5mm<sup>2</sup> x 6mm Ferrule - Orange

- Funnel feed-in made of polypropylene
- Heat resistant up to 120 °C
- For wires from 0.14...4 mm<sup>2</sup>
- Material: E-Cu/A-Cu, galvanically tin-plated



### Product description

European manufactured, this range ensures a reliable crimp without splitting.

### Specifications

<b>Color</b>	Orange
<b>Conductor tube</b>	Copper alloy
<b>Contact surface</b>	Galvanic tin-plated, shiny
<b>Country of origin</b>	DE
<b>Cross Section Max</b>	0.5
<b>Diameter of collar</b>	2.6
<b>Diameter of tube</b>	1
<b>DIN 46228-1:1992</b>	No
<b>DIN 46228-4:1990</b>	Yes
<b>Length</b>	12
<b>Length of tube</b>	6
<b>Operating temperature from</b>	-5
<b>Operating temperature to</b>	105
<b>Pack Size</b>	500

Plastic collar	Polypropylene-homopolymer
Rated wire cross section to (AWG)	20
Standard	German Standard
Stripping Length	8
Tariff code	85369010
Thickness of collar	0.25
Thickness of tube	0.15
Weight	0.07

