


## INSULATED BOOTLACE FERRULES

### 0.14MM<sup>2</sup> TO 4MM<sup>2</sup>

V30AE004158

0.5mm<sup>2</sup> x 12mm Ferrule - Orange

- Funnel feed-in made of polypropylene
- Heat resistant up to 120 °C
- For wires from 0.14...4 mm<sup>2</sup>
- Material: E-Cu/A-Cu, galvanically tin-plated





#### Product description

European manufactured, this range ensures a reliable crimp without splitting.

#### Specifications

<b>Color</b>	Orange
<b>Conductor tube</b>	Copper alloy
<b>Contact surface</b>	Galvanic tin-plated, shiny
<b>Country of origin</b>	DE
<b>Cross Section Max</b>	0.5
<b>Diameter of collar</b>	2.6
<b>Diameter of tube</b>	1
<b>DIN 46228-1:1992</b>	No
<b>DIN 46228-4:1990</b>	Yes
<b>Length</b>	18
<b>Length of tube</b>	12
<b>Operating temperature from</b>	-5
<b>Operating temperature to</b>	105
<b>Pack Size</b>	500

Plastic collar	Polypropylene-homopolymer
Rated wire cross section to (AWG)	20
Standard	German Standard
Stripping Length	14
Tariff code	85369010
Thickness of collar	0.25
Thickness of tube	0.15
Weight	0.11



Bezeichnung Description	AWG	Teilcode/Teil-Nr. Order code/Order no.	DN	RDS	h <sub>1</sub>	h <sub>2</sub>	h <sub>3</sub>	h <sub>4</sub>	h <sub>5</sub>	h <sub>6</sub>	VPE
0.14 8 N 25	V30AE020907	V30AE020909	10	6	0.6	0.15	1.5	0.25	500		
0.14 8 L 25	V30AE020908	V30AE020901	12	8	0.6	0.15	1.5	0.25	500		
0.25 8 N 24	V30AE030001	V30AE030002	10	6	0.85	0.15	1.8	0.25	500		
		V30AE030044									
0.25 8 L 24	V30AE030002	V30AE030003	12	8	0.85	0.15	1.8	0.25	500		
		V30AE030045									
0.25 12 L3 24	V30AE020485	V30AE020486	16	12	0.65	0.15	1.8	0.25	500		
		V30AE020504									
0.34 8 N 22	V30AE030003	V30AE030005	10	6	0.85	0.15	2	0.25	500		
		V30AE030035									
0.34 8 L 22	V30AE030004	V30AE030006	12	8	0.85	0.15	2	0.25	500		
		V30AE030077									
0.34 12 L3 22	V30AE030486	V30AE030487	16	12	0.85	0.15	2	0.25	500		
0.5 8 K 20	V30AE030005	V30AE030007	12	6	1	0.15	2.8	0.25	500		
0.5 8 N 20	V30AE030005	V30AE030008	14	8	1	0.15	2.8	0.25	500		
0.5 10 HL 20	V30AE030007	V30AE030009	16	10	1	0.15	2.8	0.25	500		
0.5 12 L 20	V30AE030486	V30AE030488	16	12	1	0.15	2.8	0.25	500		
0.75 8 K 18	V30AE030008	V30AE030040	12	6	1.2	0.15	3.8	0.25	500		
0.75 8 N 18	V30AE030009	V30AE030041	14	8	1.2	0.15	3.8	0.25	500		
0.75 9 H4S 18	V30AE030087	V30AE030088	16	9	1.2	0.15	3.8	0.25	500		
0.75 10 HL 18	V30AE030090	V30AE030091	16	10	1.2	0.15	3.8	0.25	500		
0.75 10 HL 18	V30AE030090	V30AE030092	16	10	1.2	0.15	3.8	0.25	500		
0.75 12 L 18	V30AE030001	V30AE030043	16	12	1.2	0.15	3.8	0.25	500		
1 8 K 15	V30AE030012	V30AE030044	12	6	1.4	0.15	3	0.25	500		
1 8 N 15	V30AE030013	V30AE030045	14	8	1.4	0.15	3	0.25	500		
1 10 HL 15	V30AE030014	V30AE030046	16	10	1.4	0.15	3	0.25	500		
1 12 L 15	V30AE030015	V30AE030047	16	12	1.4	0.15	3	0.25	500		
1.5 8 K 15	V30AE030016	V30AE030048	12	6	1.7	0.15	3.5	0.25	500		
1.5 8 N 15	V30AE030017	V30AE030049	14	8	1.7	0.15	3.5	0.25	500		
1.5 10 HL 15	V30AE030018	V30AE030050	16	10	1.7	0.15	3.5	0.25	500		

Bezeichnung Description	AWG	Teilcode/Teil-Nr. Order code/Order no.	DN	RDS	h <sub>1</sub>	h <sub>2</sub>	h <sub>3</sub>	h <sub>4</sub>	h <sub>5</sub>	h <sub>6</sub>	VPE
0.14 8 N 25	V30AE020907	V30AE020909	10	6	0.6	0.15	1.5	0.25	500		
0.14 8 L 25	V30AE020908	V30AE020901	12	8	0.6	0.15	1.5	0.25	500		
0.25 8 N 24	V30AE030001	V30AE030002	10	6	0.85	0.15	1.8	0.25	500		
		V30AE030044									
0.25 8 L 24	V30AE030002	V30AE030003	12	8	0.85	0.15	1.8	0.25	500		
		V30AE030045									
0.25 12 L3 24	V30AE020485	V30AE020486	16	12	0.65	0.15	1.8	0.25	500		
		V30AE020504									
0.34 8 N 22	V30AE030003	V30AE030005	10	6	0.85	0.15	2	0.25	500		
		V30AE030035									
0.34 8 L 22	V30AE030004	V30AE030006	12	8	0.85	0.15	2	0.25	500		
		V30AE030077									
0.34 12 L3 22	V30AE030486	V30AE030487	16	12	0.85	0.15	2	0.25	500		
0.5 8 K 20	V30AE030005	V30AE030007	12	6	1	0.15	2.8	0.25	500		
0.5 8 N 20	V30AE030005	V30AE030008	14	8	1	0.15	2.8	0.25	500		
0.5 10 HL 20	V30AE030007	V30AE030009	16	10	1	0.15	2.8	0.25	500		
0.5 12 L 20	V30AE030486	V30AE030488	16	12	1	0.15	2.8	0.25	500		
0.75 8 K 18	V30AE030008	V30AE030040	12	6	1.2	0.15	3.8	0.25	500		
0.75 8 N 18	V30AE030009	V30AE030041	14	8	1.2	0.15	3.8	0.25	500		
0.75 9 H4S 18	V30AE030087	V30AE030088	16	9	1.2	0.15	3.8	0.25	500		
0.75 10 HL 18	V30AE030090	V30AE030091	16	10	1.2	0.15	3.8	0.25	500		
0.75 10 HL 18	V30AE030090	V30AE030092	16	10	1.2	0.15	3.8	0.25	500		
0.75 12 L 18	V30AE030001	V30AE030043	16	12	1.2	0.15	3.8	0.25	500		
1 8 K 15	V30AE030012	V30AE030044	12	6	1.4	0.15	3	0.25	500		
1 8 N 15	V30AE030013	V30AE030045	14	8	1.4	0.15	3	0.25	500		
1 10 HL 15	V30AE030014	V30AE030046	16	10	1.4	0.15	3	0.25	500		
1 12 L 15	V30AE030015	V30AE030047	16	12	1.4	0.15	3	0.25	500		
1.5 8 K 15	V30AE030016	V30AE030048	12	6	1.7	0.15	3.5	0.25	500		
1.5 8 N 15	V30AE030017	V30AE030049	14	8	1.7	0.15	3.5	0.25	500		
1.5 10 HL 15	V30AE030018	V30AE030050	16	10	1.7	0.15	3.5	0.25	500		