


INSULATED BOOTLACE FERRULES 0.14MM² TO 4MM²

V30AE000049

1.5mm² x 10mm Ferrule - Black

- Funnel feed-in made of polypropylene
- Heat resistant up to 120 °C
- For wires from 0.14...4 mm²
- Material: E-Cu/A-Cu, galvanically tin-plated



Product description

European manufactured, this range ensures a reliable crimp without splitting.

Specifications

| | |
|-----------------------------------|----------------------------|
| Color | Black |
| Conductor tube | Copper alloy |
| Contact surface | Galvanic tin-plated, shiny |
| Country of origin | DE |
| Cross Section Max | 1.5 |
| Diameter of collar | 3.5 |
| Diameter of tube | 1.7 |
| DIN 46228-1:1992 | No |
| DIN 46228-4:1990 | Yes |
| Length | 16 |
| Length of tube | 10 |
| Operating temperature from | -5 |
| Operating temperature to | 105 |
| Pack Size | 500 |

| | |
|-----------------------------------|---------------------------|
| Plastic collar | Polypropylene-homopolymer |
| Rated wire cross section to (AWG) | 16 |
| Standard | UL (DIN)/French Standard |
| Stripping Length | 12 |
| Tariff code | 85369010 |
| Thickness of collar | 0.25 |
| Thickness of tube | 0.15 |
| Weight | 0.14 |

