


## INSULATED BOOTLACE FERRULES

### 0.14MM<sup>2</sup> TO 4MM<sup>2</sup>

V30AE003702

2.5mm<sup>2</sup> x 10mm Ferrule - Blue

- Funnel feed-in made of polypropylene
- Heat resistant up to 120 °C
- For wires from 0.14...4 mm<sup>2</sup>
- Material: E-Cu/A-Cu, galvanically tin-plated



#### Product description

European manufactured, this range ensures a reliable crimp without splitting.

#### Specifications

<b>Color</b>	Blue
<b>Conductor tube</b>	Copper alloy
<b>Contact surface</b>	Galvanic tin-plated, shiny
<b>Country of origin</b>	DE
<b>Cross Section Max</b>	2.5
<b>Diameter of collar</b>	4.2
<b>Diameter of tube</b>	2.2
<b>DIN 46228-1:1992</b>	No
<b>DIN 46228-4:1990</b>	Yes
<b>Length</b>	17
<b>Length of tube</b>	10
<b>Operating temperature from</b>	-5
<b>Operating temperature to</b>	105
<b>Pack Size</b>	500

Plastic collar	Polypropylene-homopolymer
Rated wire cross section to (AWG)	14
Standard	German/UL (DIN) Standard
Stripping Length	12
Tariff code	85369010
Thickness of collar	0.25
Thickness of tube	0.15
Weight	0.21

