


INSULATED BOOTLACE FERRULES

0.14MM² TO 4MM²

V30AE000055

Bootlace Ferrules 4sq-10mm Grey (Pack 500)

- Funnel feed-in made of polypropylene
- Heat resistant up to 120 °C
- For wires from 0.14...4 mm²
- Material: E-Cu/A-Cu, galvanically tin-plated





Product description

European manufactured, this range ensures a reliable crimp without splitting.

Specifications

Color	Grey
Conductor tube	Copper alloy
Contact surface	Galvanic tin-plated, shiny
Country of origin	DE
Cross Section Max	4
Diameter of collar	4.8
Diameter of tube	2.8
DIN 46228-1:1992	No
DIN 46228-4:1990	Yes
Length	18
Length of tube	10
Operating temperature from	-5
Operating temperature to	105
Pack Size	500

Plastic collar	Polypropylene-homopolymer
Rated wire cross section to (AWG)	12
Standard	German/UL (DIN) Standard
Stripping Length	12
Tariff code	85369010
Thickness of collar	0.3
Thickness of tube	0.2
Weight	0.27



Bezeichnung Description	AWG	Teilcode/Teil-Nr. Colour code/Colour no.	DR	RDS	Le	La	RL	RL	RL	RL	WPE
0.14 8 N 25	V30AE000907	V30AE000909	10	6	0.6	0.15	1.5	0.25	500		
0.14 8 L 25	V30AE000908	V30AE000901	12	8	0.6	0.15	1.5	0.25	500		
0.25 8 N 24	V30AE000001	V30AE000002	10	6	0.85	0.15	1.8	0.25	500		
0.25 8 L 24	V30AE000002	V30AE000003	12	8	0.85	0.15	1.8	0.25	500		
0.25 12 LS 24	V30AE000405	V30AE000406	16	12	0.85	0.15	1.8	0.25	500		
0.34 8 N 22	V30AE000003	V30AE000004	10	6	0.85	0.15	2	0.25	500		
0.34 8 L 22	V30AE000004	V30AE000005	12	8	0.85	0.15	2	0.25	500		
0.34 12 LS 22	V30AE000406	V30AE000407	16	12	0.85	0.15	2	0.25	500		
0.5 8 K 20	V30AE000005	V30AE000007	12	8	1	0.15	2.8	0.25	500		
0.5 8 N 20	V30AE000005	V30AE000008	14	8	1	0.15	2.8	0.25	500		
0.5 10 HL 20	V30AE000007	V30AE000009	16	10	1	0.15	2.8	0.25	500		
0.5 12 L 20	V30AE000406	V30AE000408	16	12	1	0.15	2.8	0.25	500		
0.75 8 N 18	V30AE000008	V30AE000009	12	8	1.2	0.15	3.8	0.25	500		
0.75 8 N 18	V30AE000009	V30AE000010	14	8	1.2	0.15	3.8	0.25	500		
0.75 9 HLS 18	V30AE000009	V30AE000011	16	9	1.2	0.15	3.8	0.25	500		
0.75 10 HL 18	V30AE000010	V30AE000012	16	10	1.2	0.15	3.8	0.25	500		
0.75 12 L 18	V30AE000011	V30AE000013	16	12	1.2	0.15	3.8	0.25	500		
1 8 K 16	V30AE000012	V30AE000014	12	8	1.4	0.15	3	0.25	500		
1 8 N 16	V30AE000012	V30AE000015	14	8	1.4	0.15	3	0.25	500		
1 10 HL 16	V30AE000014	V30AE000016	16	10	1.4	0.15	3	0.25	500		
1 12 L 16	V30AE000015	V30AE000017	16	12	1.4	0.15	3	0.25	500		
1.5 8 K 16	V30AE000016	V30AE000018	12	8	1.7	0.15	3.5	0.25	500		
1.5 8 N 16	V30AE000016	V30AE000019	14	8	1.7	0.15	3.5	0.25	500		
1.5 10 HL 16	V30AE000017	V30AE000020	16	10	1.7	0.15	3.5	0.25	500		

Bezeichnung Description	AWG	Teilcode/Teil-Nr. Colour code/Colour no.	DR	RDS	Le	La	RL	RL	RL	RL	WPE
0.14 8 N 25	V30AE000907	V30AE000909	10	6	0.6	0.15	1.5	0.25	500		
0.14 8 L 25	V30AE000908	V30AE000901	12	8	0.6	0.15	1.5	0.25	500		
0.25 8 N 24	V30AE000001	V30AE000002	10	6	0.85	0.15	1.8	0.25	500		
0.25 8 L 24	V30AE000002	V30AE000003	12	8	0.85	0.15	1.8	0.25	500		
0.25 12 LS 24	V30AE000405	V30AE000406	16	12	0.85	0.15	1.8	0.25	500		
0.34 8 N 22	V30AE000003	V30AE000004	10	6	0.85	0.15	2	0.25	500		
0.34 8 L 22	V30AE000004	V30AE000005	12	8	0.85	0.15	2	0.25	500		
0.34 12 LS 22	V30AE000406	V30AE000407	16	12	0.85	0.15	2	0.25	500		
0.5 8 K 20	V30AE000005	V30AE000007	12	8	1	0.15	2.8	0.25	500		
0.5 8 N 20	V30AE000005	V30AE000008	14	8	1	0.15	2.8	0.25	500		
0.5 10 HL 20	V30AE000007	V30AE000009	16	10	1	0.15	2.8	0.25	500		
0.5 12 L 20	V30AE000406	V30AE000408	16	12	1	0.15	2.8	0.25	500		
0.75 8 N 18	V30AE000008	V30AE000009	12	8	1.2	0.15	3.8	0.25	500		
0.75 8 N 18	V30AE000009	V30AE000010	14	8	1.2	0.15	3.8	0.25	500		
0.75 9 HLS 18	V30AE000009	V30AE000011	16	9	1.2	0.15	3.8	0.25	500		
0.75 10 HL 18	V30AE000010	V30AE000012	16	10	1.2	0.15	3.8	0.25	500		
0.75 12 L 18	V30AE000011	V30AE000013	16	12	1.2	0.15	3.8	0.25	500		
1 8 K 16	V30AE000012	V30AE000014	12	8	1.4	0.15	3	0.25	500		
1 8 N 16	V30AE000012	V30AE000015	14	8	1.4	0.15	3	0.25	500		
1 10 HL 16	V30AE000014	V30AE000016	16	10	1.4	0.15	3	0.25	500		
1 12 L 16	V30AE000015	V30AE000017	16	12	1.4	0.15	3	0.25	500		
1.5 8 K 16	V30AE000016	V30AE000018	12	8	1.7	0.15	3.5	0.25	500		
1.5 8 N 16	V30AE000016	V30AE000019	14	8	1.7	0.15	3.5	0.25	500		
1.5 10 HL 16	V30AE000017	V30AE000020	16	10	1.7	0.15	3.5	0.25	500		