


## INSULATED BOOTLACE FERRULE FOR DUAL CABLES

V30AE003116

Bootlace Ferrules 2x2.5-13 (Pack 250) grey

- Funnel feed-in made of polypropylene
- Heat resistant up to 120 °C
- For wires from 0.5...16 mm<sup>2</sup>
- Material: E-Cu/A-Cu, galvanically tin-plated



### Product description

### Specifications

<b>Color</b>	Grey
<b>Conductor tube</b>	Copper alloy
<b>Contact surface</b>	Galvanic tin-plated, shiny
<b>Country of origin</b>	EEC
<b>Cross Section Max</b>	2.5
<b>Diameter of tube</b>	2.8
<b>DIN 46228-1:1992</b>	No
<b>DIN 46228-4:1990</b>	Yes
<b>Length</b>	21
<b>Length of tube</b>	12
<b>Operating temperature from</b>	-5
<b>Operating temperature to</b>	105
<b>Pack Size</b>	100
<b>Plastic collar</b>	Polypropylene-homopolymer
<b>Rated wire cross section to (AWG)</b>	14
<b>Standard</b>	French Standard

Stripping Length	15
Tariff code	85369010
Thickness of collar	0.4
Thickness of tube	0.15
Weight	0.22

