

INSULATED FERRULES ON REEL

V30MA000033

0.5mm² x 8mm Ferrule - White (Reel 5000)

- Tin-plated copper for strong conductivity.
- No need to change tools or machines.
- Ideal for high-speed automated crimping.
- Sizes: 0.34–2.5 mm², 8–10 mm length.
- Gas-tight, vibration-proof crimps.



PRODUCT DESCRIPTION

Z+F Ferrules on Reel are designed to make wire termination fast, neat, and reliable – ideal for use in automated production environments. These ferrules suit wire sizes from 0.34 to 2.5 mm² (AWG 22–14) and are made from high-quality tin-plated copper with a durable plastic collar. They fully comply with DIN 46228 Part 4 standards, ensuring consistent performance and safety.

SPECIFICATIONS

Color	White
Country of origin	DE
Cross Section Max	0.5
Diameter of collar	2.6
Diameter of tube	1
DIN 46228-1:1992	No
DIN 46228-4:1990	Yes
Length	14
Length of tube	8
Operating temperature from	-5
Operating temperature to	105
Pack Size	1
Rated wire cross section to (AWG)	20
Stripping Length	10
Tariff code	85369010

Thickness of collar	0.25
Thickness of tube	0.15
Weight	0.12

Beschreibung	L ₁	Typ	ANG	Turnmaß in mm Teil # mm	Farbcode/Bestell-Nr.			Nennmaße mm					Rück- Plätze	
					Zuf.	DN	RDR	L	L ₁	d	S	d ₁		S ₁
0.34 B N 22	240			VISMA000012				10	8	0.85	0.15	2	0.25	5000
0.34 B L 22	240			VISMA000012				12	8	0.85	0.15	2	0.25	5000
0.5 B N 20	320			VISMA000034	VISMA000033	VISMA000033		14	8	1	0.18	2.6	0.25	5000
0.5 B L 20	320			VISMA000034	VISMA000033	VISMA000033		14	8	1	0.18	2.6	0.25	5000
0.5 B N 18	320			VISMA000018	VISMA000017	VISMA000017		10	10	1	0.15	2.6	0.25	5000
0.5 B L 18	320			VISMA000018	VISMA000017	VISMA000017		10	10	1	0.15	2.6	0.25	5000
0.75 B N 16	320			VISMA000016	VISMA000015	VISMA000015		14	8	1.2	0.16	2.6	0.25	5000
0.75 B L 16	320			VISMA000016	VISMA000015	VISMA000015		14	8	1.2	0.16	2.6	0.25	5000
1 B N 16	320			VISMA000016	VISMA000015	VISMA000015		10	10	1.2	0.16	2.6	0.25	5000
1 B L 16	320			VISMA000016	VISMA000015	VISMA000015		10	10	1.2	0.16	2.6	0.25	5000
1.3 B N 16	320			VISMA000016	VISMA000015	VISMA000015		14	8	1.4	0.16	3	0.25	5000
1.3 B L 16	320			VISMA000016	VISMA000015	VISMA000015		14	8	1.4	0.16	3	0.25	5000
1.5 B N 16	320			VISMA000016	VISMA000015	VISMA000015		14	8	1.7	0.16	3.5	0.25	5000
1.5 B L 16	320			VISMA000016	VISMA000015	VISMA000015		14	8	1.7	0.16	3.5	0.25	5000
1.5 B N 14	320			VISMA000014	VISMA000013	VISMA000013		14	8	2.2	0.16	4.2	0.25	5000
1.5 B L 14	320			VISMA000014	VISMA000013	VISMA000013		14	8	2.2	0.16	4.2	0.25	5000
1.5 B N 14.8	320			VISMA004815	VISMA004814	VISMA004814		16	10	2.2	0.16	4.2	0.25	5000
1.5 B L 14.8	320			VISMA004815	VISMA004814	VISMA004814		16	10	2.2	0.16	4.2	0.25	5000