

INSULATED FERRULES ON REEL

V30MA000040

1.5mm² x 8mm Ferrule on Reel - Black

- Tin-plated copper for strong conductivity.
- No need to change tools or machines.
- Ideal for high-speed automated crimping.
- Sizes: 0.34–2.5 mm², 8–10 mm length.
- Gas-tight, vibration-proof crimps.



Product description

Z+F Ferrules on Reel are designed to make wire termination fast, neat, and reliable – ideal for use in automated production environments. These ferrules suit wire sizes from 0.34 to 2.5 mm² (AWG 22–14) and are made from high-quality tin-plated copper with a durable plastic collar. They fully comply with DIN 46228 Part 4 standards, ensuring consistent performance and safety.

Specifications

Color	Black
Conductor tube	Copper alloy
Contact surface	Galvanic tin-plated, shiny
Country of origin	DE
Cross Section Max	1.5
Diameter of collar	3.5
Diameter of tube	1.7
DIN 46228-1:1992	No
DIN 46228-4:1990	Yes
Length	14
Length of tube	8
Operating temperature from	-5
Operating temperature to	105
Pack Size	1

Plastic collar	Polypropylene-homopolymer
Rated wire cross section to (AWG)	16
Stripping Length	10
Tariff code	85369010
Thickness of collar	0.25
Thickness of tube	0.15
Weight	0.2