

INSULATED FERRULES ON REEL

V30MA000037

0.75mm² x 8mm Ferrule Reel - Light Blue

- Tin-plated copper for strong conductivity.
- No need to change tools or machines.
- Ideal for high-speed automated crimping.
- Sizes: 0.34–2.5 mm², 8–10 mm length.
- Gas-tight, vibration-proof crimps.



Product description

Z+F Ferrules on Reel are designed to make wire termination fast, neat, and reliable – ideal for use in automated production environments. These ferrules suit wire sizes from 0.34 to 2.5 mm² (AWG 22–14) and are made from high-quality tin-plated copper with a durable plastic collar. They fully comply with DIN 46228 Part 4 standards, ensuring consistent performance and safety.

Specifications

Color	Blue
Conductor tube	Copper alloy
Contact surface	Galvanic tin-plated, shiny
Country of origin	DE
Cross Section Max	0.75
Diameter of collar	2.8
Diameter of tube	1.2
DIN 46228-1:1992	No
DIN 46228-4:1990	Yes
Length	14
Length of tube	8
Operating temperature from	-5
Operating temperature to	105
Pack Size	500

Plastic collar	Polypropylene-homopolymer
Rated wire cross section to (AWG)	18
Standard	French Standard
Stripping Length	10
Tariff code	85369010
Thickness of collar	0.25
Thickness of tube	0.15
Weight	0.1

Beschreibung		AWG	Tunnel ø mm Feil ø mm	Partcode/Reise-Nr. Colour code/Order no.				Nennweite mm Dimensions mm				Back Pieces	
mmF	L ₁ Tgr TgrF			ZuF	DN	KBR	L	L ₁	ø	S	ø ₁		S ₁
0.34	8	N	22	240	V30MA000012		10	8	0.85	0.15	2	0.25	5000
0.34	8	L	22	240	V30MA000012		12	8	0.85	0.15	2	0.25	5000
0.5	8	N	20	320	V30MA000034	V30MA000033	14	8	1	0.18	2.6	0.25	5000
0.5	10	HL	20	320	V30MA000036	V30MA000035	16	10	1	0.15	2.6	0.25	5000
0.75	8	N	18	320	V30MA000038	V30MA000037	14	8	1.2	0.16	2.8	0.25	5000
0.75	10	HL	18	320	V30MA000038	V30MA000037	16	10	1.2	0.16	2.8	0.25	5000
1	8	N	16	320	V30MA000039	V30MA000038	14	8	1.4	0.16	3	0.25	5000
1	10	HL	16	320	V30MA000039	V30MA000038	16	10	1.4	0.16	3	0.25	5000
1.5	8	N	16	320	V30MA000041	V30MA000040	14	8	1.7	0.16	3.5	0.25	5000
1.5	10	HL	16	320	V30MA000041	V30MA000040	16	10	1.7	0.16	3.5	0.25	5000
2.5	8	N	14	320	V30MA000043	V30MA000042	14	8	2.2	0.16	4.2	0.25	3000
2.5	10	HL	14	320	V30MA000043	V30MA000042	16	10	2.2	0.16	4.2	0.25	3000
3.5	8	N	12	320	V30MA000045	V30MA000044	14	8	2.8	0.16	4.8	0.25	3000
3.5	10	HL	12	320	V30MA000045	V30MA000044	16	10	2.8	0.16	4.8	0.25	3000