



CHROME MODULAR POWER SUPPLY 24VDC

24VDC, 0.42-3.8A, 10-92W

DRC-24V10W1AZ

Power Supply Chrome 24VDC 10W 0.42A

- Width 18, 53, 71 and 89.9 mm
- Efficiency >80%
- NEC Class 2
- Din Rail Mount



PRODUCT DESCRIPTION

SPECIFICATIONS

Approvals	CB, CE, NEC Class 2, TÜV, UL
Depth	55.6
Effect	10
Efficiency	80
Height	91
Hold-up time at 120 V AC, full load. Typical.	10
Hold-up time at 230 V AC, full load. Typical.	60
Input voltage AC	100-240 V
Input voltage ac max	264
Input voltage ac min	90
Input voltage DC	125-375 V
Input voltage dc max	375
Input voltage dc min	125
Inrush current at 120 V ac typical	15
Inrush current at 230 V ac typical	30
IP Class	IP20

Output Current	0.42
Output voltage	24
Output voltage max	24
Output voltage min	24
Power Consumption At 120 V AC	0.3
Power Consumption At 230 V AC	0.2
Supply Frequency	50-60 Hz
Temperature Range Without Derating From	-25
Temperature Range Without Derating To	55
Weight	0.065
Width	18

