



## CHROME MODULAR POWER SUPPLY 24VDC

24VDC, 0.42-3.8A, 10-92W

DRC-24V30W1AZ

- Width 18, 53, 71 and 89.9 mm
- Efficiency >80%
- NEC Class 2
- Din Rail Mount



### Product description

### Specifications

<b>Approvals</b>	CB, CE, NEC Class 2, TÜV, UL
<b>Depth</b>	55.6
<b>Effect</b>	30
<b>Efficiency</b>	87
<b>Height</b>	91
<b>Hold-up time at 120 V AC, full load. Typical.</b>	25
<b>Hold-up time at 230 V AC, full load. Typical.</b>	60
<b>Input voltage AC</b>	100-240 V
<b>Input voltage ac max</b>	264
<b>Input voltage ac min</b>	90
<b>Input voltage DC</b>	125-375 V
<b>Input voltage dc max</b>	375
<b>Input voltage dc min</b>	125
<b>Inrush current at 120 V ac typical</b>	25
<b>Inrush current at 230 V ac typical</b>	50
<b>IP Class</b>	IP20

<b>Output Current</b>	1.25
<b>Output voltage</b>	24
<b>Output voltage max</b>	24.48
<b>Output voltage min</b>	23.52
<b>Power Consumption At 120 V AC</b>	0.8
<b>Power Consumption At 230 V AC</b>	0.6
<b>Supply Frequency</b>	50-60 Hz
<b>Temperature Range Without Derating From</b>	-25
<b>Temperature Range Without Derating To</b>	55
<b>Weight</b>	0.14
<b>Width</b>	53

**CHROME** Chrome DIN Rail Power Supply  
24V 30W 1 Phase / DRC-24V30W1AZ

