



CHROME MODULAR POWER SUPPLY 24VDC

24VDC, 0.42-3.8A, 10-92W

DRC-24V100W1AZ

- Width 18, 53, 71 and 89.9 mm
- Efficiency >80%
- NEC Class 2
- Din Rail Mount



Product description

Specifications

Approvals	CB, CE, NEC Class 2, TÜV, UL
Depth	55.6
Effect	91.2
Efficiency	89
Height	91
Hold-up time at 120 V AC, full load. Typical.	10
Hold-up time at 230 V AC, full load. Typical.	60
Input voltage AC	100-240 V
Input voltage ac max	264
Input voltage ac min	90
Input voltage DC	125-375 V
Input voltage dc max	375
Input voltage dc min	125
Inrush current at 120 V ac typical	30
Inrush current at 230 V ac typical	60
IP Class	IP20

Output Current	3.8
Output voltage	24
Output voltage max	24
Output voltage min	22
Power Consumption At 120 V AC	2.2
Power Consumption At 230 V AC	1
Supply Frequency	50-60 Hz
Temperature Range Without Derating From	-25
Temperature Range Without Derating To	55
Weight	0.35
Width	89.9

CHROME Chrome DIN Rail Power Supply
24V 100W 1 Phase / DRC-24V100W1AZ

