



CHROME MODULAR POWER SUPPLY 12VDC

12VDC, 0.83-6A, 9.96-72W

DRC-12V100W1AZ

- Width 18, 53, 71 and 89.9 mm
- Efficiency >80%
- NEC Class 2
- Din rail mount



Product description

Specifications

Approvals	CB, CE, TÜV, UL
Depth	55.6
Effect	72
Efficiency	86
Height	91
Hold-up time at 120 V AC, full load. Typical.	20
Hold-up time at 230 V AC, full load. Typical.	100
Input voltage AC	100-240 V
Input voltage ac max	264
Input voltage ac min	90
Input voltage DC	125-375 V
Input voltage dc max	375
Input voltage dc min	125
Inrush current at 120 V ac typical	30
Inrush current at 230 V ac typical	60
IP Class	IP20

Output Current	6
Output voltage	12
Output voltage max	14
Output voltage min	12
Power Consumption At 120 V AC	1.5
Power Consumption At 230 V AC	0.9
Supply Frequency	50-60 Hz
Temperature Range Without Derating From	-25
Temperature Range Without Derating To	55
Weight	0.36
Width	89.9

CHROME Chrome DIN Rail Power Supply
12V 100W 1 Phase / DRC-12V100W1AZ

