

FIEPOS BASIC 3-PHASE

3x 380-480 V AC/24-28 V DC, 300 and 500 W

FPT300.242-002-101
IP65/IP67 Power supply 3x380-480 V AC/24 V DC, 300 W

- IP54 or IP65/IP67
- Efficiency >95%
- Output power 360/600 W
- 600/1000 Wpeak 5s
- IO-Link or DC-OK relay



PRODUCT DESCRIPTION

The FPT300 is an industrial grade power supply for 3-phase networks and is incorporated in to a rugged wall-mount housing with IP65/67 protection. It provides one floating, stabilized SELV/PELV output, which is galvanically separated from the input. In case of an overload or load failure, the output offers hiccup-mode.

The most outstanding features of the FPS series are the compact size, the wide operational temperature range, the low input inrush current and the extremely high efficiencies, which are achieved by various technological design technologies.

SPECIFICATIONS

Active Transient	Yes
Approvals	CB, CE, cULus
Back-feeding loads	35V / 4,3 J
DC relay output	Yes
DC-OK/IO-link connector	M12-A
Depth	59
Effect	300
Efficiency At 400 V AC, full load. Typical	95
Efficiency At 400 V AC. Typical	93.6
Height	183
Hold-up time at 400 V AC, full load. Typical.	25
Input connector	HAN Q4/2
Input voltage AC	380-480

Input voltage ac max	552
Input voltage ac min	323
Inrush current at 400 V ac typical	2
IO-LINK	No
IP Class	IP65, IP67
Lifetime at 400 V ac, full load and +40 ° C	235000
MTBF (IEC 61709) 400 V ac, max loan, +40 °C	838000
Number of phases	3
Output connectors	1x HAN Q4/0
Output Current	12.5
Output current max	25
Output voltage	24
Output voltage max	24
Output voltage min	24
Power consumption at 400 V ac	0.5
Power drop from +55 °C to + 70 °C	10
Power Factor at 400 V AC, full load. Typical	0.9
Ripple. max	100
Series	FIEPOS Basic
Supply Frequency	50-60 Hz ±6 %
Temperature Range Without Derating From	-25
Temperature Range Without Derating To	55
Total output power <+45°C	360
Total output power <+55°C	300
Total output power <+70°C	150
Total output power <1 min	484
Total output power <1 s	640
Total output power <5 s, <+55°C	600
Weight	1.2
Width	182

