



## CHROME II MODULAR POWER SUPPLY 24VDC

DRC-24V060W1RZ

PSU Chrome II 100-240VAC/24VDC, 60W/2,5A

- Stable 24V DC output Ideal for PLCs, relays, sensors and automation components that rely on consistent voltage.
- Modular, space-saving design Small footprint that fits easily into compact or modular control panels.
- High efficiency with low heat Reduces energy loss and improves long-term reliability.



### Product description

The Chrome II 24VDC modular power supply is built for installers who want dependable power in a clean, space-saving format. It delivers stable 24V output for PLCs, sensors, relays, actuators, instrumentation and general automation equipment.

What this really means is you get a PSU that runs cool, handles fluctuating loads and protects your downstream devices against electrical faults. Its compact modular design makes it perfect for small control panels or applications where every millimetre of DIN-rail matters.

### Specifications

<b>Approvals</b>	BSMI, CB, CCC, CE, UKCA, NEC Class 2, REACH, RoHS, TÜV, UL
<b>Clamp type</b>	Screw
<b>Depth</b>	55
<b>Effect</b>	60
<b>Efficiency</b>	89.5
<b>Height</b>	87.5
<b>Hold-up time at 120 V AC, full load. Typical.</b>	16
<b>Hold-up time at 230 V AC, full load. Typical.</b>	80
<b>Input voltage AC</b>	100-240 V
<b>Input voltage ac max</b>	264
<b>Input voltage ac min</b>	85
<b>Inrush current at 230 V ac typical</b>	40
<b>IP Class</b>	IP20

<b>Material Protection</b>	Plastic
<b>Output Current</b>	2.5
<b>Output voltage</b>	24
<b>Output voltage max</b>	26.4
<b>Output voltage min</b>	21.6
<b>Power Consumption At 120 V AC</b>	1.3
<b>Power Consumption At 230 V AC</b>	0.9
<b>Supply Frequency</b>	50-60 Hz
<b>Temperature Range Without Derating From</b>	-30
<b>Temperature Range Without Derating To</b>	70
<b>Weight</b>	0.17
<b>Width</b>	52.5

