CHROME II MODULAR POWER SUPPLY 24VDC

DRC-24V015W1RZ
PSU Chrome II 100-240VAC/24VDC,15W/0,63A



- Stable 24V DC output Ideal for PLCs, relays, sensors and automation components that rely on consistent voltage.
- Modular, space-saving design Small footprint that fits easily into compact or modular control panels.
- High efficiency with low heat Reduces energy loss and improves long-term reliability.

PRODUCT DESCRIPTION

The Chrome II 24VDC modular power supply is built for installers who want dependable power in a clean, space-saving format. It delivers stable 24V output for PLCs, sensors, relays, actuators, instrumentation and general automation equipment.

What this really means is you get a PSU that runs cool, handles fluctuating loads and protects your downstream devices against electrical faults. Its compact modular design makes it perfect for small control panels or applications where every millimetre of DIN-rail matters.

SPECIFICATIONS

Approvals	BSMI, CB, CCC, CE, NEC Class 2, REACH, RoHS, TÜV, UL
Depth	55
Effect	15
Efficiency	875
Height	875
Hold-up time at 120 V AC, full load. Typical.	18
Hold-up time at 230 V AC, full load. Typical.	79
Input voltage AC	100-240 V
Input voltage ac max	264
Input voltage ac min	85
Input voltage DC	125-375 V
Input voltage dc max	375
Input voltage dc min	125

Inrush current at 230 V ac typical	40
IP Class	IP20
Output Current	63
Output voltage	24
Output voltage max	264
Output voltage min	216
Power Consumption At 120 V AC	5
Power Consumption At 230 V AC	3
Supply Frequency	50-60 Hz
Temperature Range Without Derating From	-40
Temperature Range Without Derating To	70
Weight	6
Width	18

